

**10 YEAR CEILING PANEL
LIMITED WARRANTY**



Armstrong World Industries Pty. Ltd. (ACN 000 361 679) guarantees the Armstrong HumiGuard Plus (RH 99) & HumiGuard Max (RH100) series acoustical material, item number (), installed in the building and in the quantities listed below, shall be free from visible sagging or warping as a direct result of defects in material or factory workmanship for 10 years from date of installation of the ceiling material, subject to the conditions set forth below:

1. The material shall be purchased from an approved distributor and installed by an approved ceiling contractor in accordance with the Armstrong Installation & Maintenance Guide.
2. Installation shall be done in areas free from excessive humidity, chemical fumes, freezing temperature and vibration.
3. Installation shall be carried out in temperature conditions 0 – 49°C (120°F) and relative humidity conditions of 0–99%. HumiGuard Plus ceilings cannot be used in exterior applications, where standing water is present or where moisture will come in direct contact with the ceiling. Ceramaguard with HumiGuard Max (RH100) performance can be installed in conditions up to 49°C

(120°F) and relative humidity conditions of 1–100%.

(Note: It is recommended that an aluminium suspension system be used with HumiGuard Max products).

Following installation, the environmental conditions shall be controlled within the said limits.

4. The product shall not be subjected to direct moisture in the form of building leaks or temperature and humidity conditions causing condensation to occur on the ceiling panel during or after installation.
5. The acoustical material shall not support any other material.
6. The acoustical material shall be mechanically suspended and shall be neither cemented nor glued to the surface of any other material.
7. The acoustical material shall be stored in a dry and clean area, protected from possible damage by rain, snow and excessive moisture. If the acoustical material is exposed to large variations of humidity or temperature, swelling and shrinkage can result. The acoustical material shall also be protected against possible impacts and abrasions and kept at least

one metre from walls. Stack the material flat on a level floor with protective panels or sheets between the material and the floor.

Should the Armstrong material sag or warp as described above, written notice within thirty (30) days after first observations of defects must be given to Armstrong World Industries Pty. Ltd., 99 Derby Street, Silverwater, NSW 2128 Australia, (P.O. Box 6765), and after inspection and/or verification, Armstrong World Industries Pty. Ltd. shall furnish new material at its own expense of the same type and grade in an amount equal to that which is deemed defective.

The furnishings of such material shall constitute the total liability of Armstrong World Industries Pty. Ltd. hereunder and, without limitation, Armstrong shall not be responsible for any installation or replacement costs or for incidental or consequential damages of any nature whatsoever.

The foregoing constitutes the entire guarantee by the Armstrong World Industries Company. All other warranties or guarantees, expressed or implied, including any guarantee that the goods are merchantable or fit for a particular purpose are hereby excluded.

Warranty

Material: (Product Type)
 (Size, Thickness and Quantity)

Building: (Name)
 (Address)
 (City) (State) (Postcode)

Ceiling Systems Contractor: (Name)
 (Address)

Date of Installation:

SIGNATURE:

General Manager
 ARMSTRONG WORLD INDUSTRIES PTY LTD ACN 000 361 679

Date: