

S-89 Asphalt Cutback Floor Tile Adhesive

▲ DANGER

**S-89 FLAMMABLE MIXTURE
EYE AND SKIN IRRITANT
VAPOR HARMFUL**

INSTALLATION:

- Vinyl Composition Tile Installation System
- Commercial/Residential

PRODUCTS:

- MultiColor
- ARTEFFECTS
- RAVE
- Stonetex
- Companion Square
- Imperial Texture
- Feature Tile/Strips
- Urethane No-Wax (Dry Back)
- SAFETY ZONE

DESCRIPTION:

- Type:** Solvent-based asphalt/cutback
- Color:** Black; contains no visible taggants
- Subfloor:** All grade levels of concrete, ceramic, terrazzo, marble, steel, stainless steel, aluminum, lead and polymeric poured floors
- Trowel:** S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart)
- Open Time:** Until dry-to-touch; 60 minutes or more
- Working Time:** 18 hours
- Spread Rate:** 350–450 sq. ft./gal. (32–41 sq. m)
- Removal from Surface:** Use clean, white cloth
Wet or dry: mineral spirits
- Advantages:** Can be used over "cutback" adhesive residue; Moisture and alkali resistant
- Shelf Life:** One year if not opened
- Freeze/Thaw Stability:** Will not freeze
- Available Units:** 5 Gal. (18.93 L)
- VOC Content:** 291 g/L; calculated and reported, SCAQMD 1168

NOTICE: STIR WELL BEFORE USING.