

# S-202 Static Dissipative Tile Adhesive

**CAUTION**

S-202 EYE AND SKIN IRRITANT

## INSTALLATION:

- SDT Installation System

## PRODUCTS:

- Static Dissipative Tile (SDT)

## DESCRIPTION:

<b>Type:</b>	Water-based/resin
<b>Color:</b>	Black; contains no visible taggants
<b>Subfloor:</b>	All grade levels of concrete; suspended wood
<b>Trowel:</b>	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart)
<b>Open Time:</b>	Until dry-to-touch; 60 minutes or more
<b>Working Time:</b>	6 hours
<b>Spread Rate:</b>	Approximately 150 sq. ft./gal. (14 sq. m)
<b>Removal from Surface:</b>	Use clean, white cloth Wet or dry: mineral spirits
<b>Advantages:</b>	Moisture and alkali resistant
<b>Shelf Life:</b>	Six months if not opened
<b>Freeze/Thaw Stability:</b>	KEEP FROM FREEZING
<b>Available Units:</b>	Gal. (3.78 L), 4 Gal. (15.14 L)
<b>VOC Content:</b>	50 g/L; calculated and reported, SCAQMD 1168

**NOTICE: STIR WELL BEFORE USING.**