

S-230 Commercial Epoxy Adhesive

▲ WARNING

S-230 EYE AND SKIN IRRITANT
MIXING OF PART A AND PART B MAY GENERATE HEAT BUILD-UP

INSTALLATION:

- Commercial Vinyl-Backed Installation System
- Vinyl Composition Tile Installation System

PRODUCTS:

- SAFETY ZONE
- SAFEGUARD
- SAFEGUARD Spa

DESCRIPTION:

- Type:** Two-part epoxy
- Color:** Amber; contains no visible taggants
- Subfloor:** All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, lead, copper, brass, bronze, and polymeric poured floors; suspended wood
- Trowel:** S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel with the S-894 Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart) S-51 Notched Spreader or 3" "S" Disposable Spreader
- Open Time:** Minimum 20 minutes
- Working Time:** One hour*
- Spread Rate:** 125–150 sq. ft./gal. (12–14 sq. m)
- Removal from Surface:** Use clean, white cloth
Wet: detergent and water
Dry: cannot be removed
- Advantages:** Moisture and alkali resistant
- Shelf Life:** One year if not opened
- Freeze/Thaw Stability:** Freeze-thaw stable to 10°F (-12°C)
- Available Units:** Gal. (two parts) (3.78 L)
- VOC Content:** Part A and Part B 30g/L; calculated and reported, SCAQMD 1168

NOTICE: DO NOT USE AT TEMPERATURES ABOVE 85°F (29°C).

* Working times vary based on job conditions, subfloors, temperature and humidity.