

S-230 Commercial Epoxy Adhesive

▲ WARNING

S-230 CAUSES EYE AND SKIN BURNS
MAY CAUSE ALLERGIC SKIN OR RESPIRATORY REACTION
VAPOR HARMFUL
MIXING OF PART A AND PART B MAY GENERATE HEAT BUILD-UP

INSTALLATION:

- Commercial Vinyl-Backed Installation System
- Vinyl Composition Tile Installation System

PRODUCTS:

- SAFETY ZONE
- SAFEGUARD
- SAFEGUARD Design
- SAFEGUARD Hydro

DESCRIPTION:

- Type:** Two-part epoxy
- Color:** Amber; contains no visible taggants
- Subfloor:** All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, lead, copper, brass, bronze, and polymeric poured floors; suspended wood
- Trowel:** S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart) S-51 Notched Spreader or 3" "S" Disposable Spreader
- Open Time:** Minimum 20 minutes
- Working Time:** One hour
- Spread Rate:** 125-150 sq. ft./gal. (12-14 sq. m)
- Removal from Surface:** Use clean, white cloth
Wet: detergent and water
Dry: cannot be removed
- Advantages:** Moisture and alkali resistant
- Shelf Life:** One year if not opened
- Available Units:** Gal. (two parts) (3.78 L)

NOTICE: DO NOT USE AT TEMPERATURES ABOVE 85°F (29°C).