

S-235 Premium Sheet Flooring Adhesive



▲ CAUTION

S-235 EYE AND SKIN IRRITANT

INSTALLATION:

- Commercial Felt-Backed Installation System
- Residential Felt-Backed Installation System

PRODUCTS:

- Highland Park
- Rhythms
- Urban Settings
- Starstep
- Candide II
- Memories
- Destinations
- Initiator
- Canyon Creek
- Enhancements
- Natural Fusion
- Station Square
- Frontgate
- MEDINTECH Tandem
- COMMISSION Plus

DESCRIPTION:

- Type:** Water-based/rubber-resin
- Color:** Cream; contains visible taggants
- Subfloor:** All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, lead, copper, brass, bronze, and polymeric poured floors; suspended wood
- Trowel:** S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel
- Open Time:** 0–20 minutes over wood and concrete; 10–20 minutes over existing flooring
- Working Time:** Up to 40 minutes
- Spread Rate:** Regular notch: 125–150 sq. ft./gal. (12–14 sq. m); fine notch: 225–275 sq. ft./gal. (20–25 sq. m)
- Removal from Surface:** Use clean, white cloth
Wet: neutral detergent and water;
Dry: mineral spirits
- Advantages:** Fast grab—prevents edge curl;
Excellent bond integrity;
Moisture and alkali resistant;
Solvent free
- Shelf Life:** One year if not opened
- Freeze/Thaw Stability:** Freeze-thaw stable to 10°F (-12°C)
- Available Units:** Qt. (946 mL), Gal. (3.78 L), 4 Gal. (15.14 L)
- VOC Content:** 4 g/L; calculated and reported, SCAQMD 1168