

S-700 Thin Spread Floor Tile Adhesive



▲ CAUTION

S-700 EYE AND SKIN IRRITANT

INSTALLATION:

- Vinyl Composition Tile Installation System
- Commercial/Residential

PRODUCTS:

- ARTEFFECTS
- Imperial Texture
- MultiColor
- Stonetex
- Companion Square
- Feature Tile/Strips
- Urethane No-Wax (Dry Back)
- SAFETY ZONE

DESCRIPTION:

Type: Water-based/asphalt-rubber
Color: Black; contains no visible taggants

Subfloor: All grade levels of concrete, ceramic, terrazzo, marble, steel, stainless steel, aluminum, lead, copper, brass and bronze; suspended wood

Trowel: S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart)

Open Time: Until dry to touch; approximately 30 minutes or more

Working Time: 18 hours

Spread Rate: 350-400 sq. ft./gal. (32-37 sq. m)

Removal from Surface: Use clean, white cloth
Wet: neutral detergent and water;
Dry: mineral spirits

Advantages: Can be used over "cutback" adhesive residue; Moisture and alkali resistant; Solvent free black asphalt emulsion; Freeze-thaw stable to 10°F (-12°C)

Shelf Life: One year if not opened

Available Units: Gal. (3.78 L), 4 Gal. (15.14 L)

NOTICE: STIR WELL BEFORE USING.