

# S-725 Wall Base Adhesive

▲ CAUTION

S-725 EYE AND SKIN IRRITANT

## INSTALLATION:

- Wall Base Installation System
- Commercial/Residential

## PRODUCTS:

- Color-Integrated Vinyl Wall Base
- Color-Integrated Rubber Wall Base
- Commercial Stair Risers

## DESCRIPTION:

- Type:** Water-based/rubber-resin
- Color:** Off-white; contains visible taggants
- Wall:** Structurally sound, dry and smooth wall surfaces
- Trowel:** S-50 Notched Spreader or 3" "L" Disposable Spreader
- Open Time:** None recommended
- Working Time:** Up to 15 minutes
- Spread Rate:** 2-1/2": 375-425 lin. ft./gal. (114-130 m lin.)  
4": 300-350 lin. ft./gal. (91-107 m lin.)  
6": 200-250 lin. ft./gal. (61-76 m lin.)  
7": 200-250 lin. ft./gal. (61-76 m lin.)
- Cartridge:**  
4": 18 lin. ft./11 oz. (5.5 m lin.)  
4": 50 lin. ft./30 oz. (15.2 m lin.)
- Removal from Surface:** Use clean, white cloth  
Wet: neutral detergent and water; Dry: mineral spirits
- Advantages:** Excellent bond integrity; Good wet strength; Freeze-thaw stable to 10°F (-12°C)
- Shelf Life:** One year if not opened
- Available Units:** Qt. (946 mL), Gal. (3.78 L), 4 Gal. (15.14 L), and 11-oz. (311.8 g) and 30-oz. (950.4 g) cartridges