

S-750 Premium Floor Tile Adhesive



▲ CAUTION

S-750 EYE AND SKIN IRRITANT

INSTALLATION:

- Vinyl Composition Tile Installation System
- Commercial/Residential
- Primer for wood and concrete with self-adhering tile

PRODUCTS:

- ARTEFFECTS
- RAVE
- Imperial Texture
- MultiColor
- Stonetex
- Companion Square
- Feature Tile/Strips
- Urethane No-Wax (Dry Back)
- Vinyl No-Wax (Dry Back)
- SAFETY ZONE

DESCRIPTION:

- Type:** Water-based/rubber-resin
- Color:** Cream; contains visible taggants
- Subfloor:** All grade levels of concrete, ceramic, terrazzo, marble and polymeric poured floors; suspended wood; wherever Tile-On Installation System is approved
- Trowel:** S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart); brush or medium-nap roller when used as primer
- Open Time:** Until dry-to-touch; approximately 30 minutes or more
- Working Time:** 6 hours*
- Spread Rate:** Trowel: 275–350 sq. ft./gal. (26–33 sq. m)
Brush or Roller (Primer): 350–400 sq. ft./gal. (33–37 sq. m)
- Removal from Surface:** Use clean, white cloth. Wet: neutral detergent and water; Dry: mineral spirits
- Advantages:** Can be used over "cutback" adhesive residue; Moisture and alkali resistant; Solvent free; Non-flammable
- Shelf Life:** One year if not opened
- Freeze/Thaw Stability:** KEEP FROM FREEZING
- Available Units:** Qt. (946 mL), Gal. (3.78 L), 4 Gal. (15.14 L)
- VOC Content:** 5 g/L; calculated and reported, SCAQMD 1168

NOTICE: STIR WELL BEFORE USING.

* Working times vary based on job conditions, subfloors, temperature and humidity.