

S-780 Linoleum Adhesive



▲ CAUTION

S-780 EYE AND SKIN IRRITANT

INSTALLATION:

- Commercial Linoleum Sheet Installation System
- Residential Linoleum Sheet Installation System

PRODUCTS:

- MARMORETTE
- GRANETTE
- COLORETTE
- UNI WALTON
- LINORETTE

DESCRIPTION:

Type:	Synthetic Polymer
Color:	White
Subfloor:	All grade levels of concrete, existing well-bonded resilient floors (not perimeter-bonded or cushion-backed), terrazzo, steel, stainless steel, aluminum, suspended wood and wood underlayments, properly mixed and applied powder underlayments and embossing levelers, primed poured in-place gypsum subfloors, radiant-heated subfloors [not to exceed 85° F (29° C)].
Trowel:	U notch (1/16" deep, 1/16" wide, 3/32" apart)
Open Time:	Porous: None Nonporous: 5–10 minutes
Working Time:	Up to 25 minutes*
Spread Rate:	120–135 sq. ft./gal. (11–12.5 sq.m)
Removal from Surface:	Use clean, white cloth. Wet: neutral detergent and water; Dry: mineral spirits
Advantages:	Moisture and alkali resistant, Rapid bond development, Excellent bond strength, Easy trowelability.
Shelf Life:	One year if not opened
Freeze/Thaw Stability:	Freeze-thaw stable to 10°F (-12°C)
Available Units:	4 Gal. (15.14 L)
VOC Content:	5.5 g/L; calculated and reported, SCAQMD 1168

* Working times vary based on job conditions, subfloors, temperature and humidity.