

S-760 Linoleum Adhesive



⚠ CAUTION

S-760 EYE AND SKIN IRRITANT

INSTALLATION:

- Commercial Linoleum Sheet Flooring Installation System
- Residential Linoleum Sheet Flooring Installation System

PRODUCTS:

- MARMORETTE
- GRANETTE
- COLORETTE
- LINORETTE
- UNI WALTON
- LINODUR
- Residential MARMORETTE

DESCRIPTION:

- Type:** Latex-based/rubber-resin
- Color:** Cream; contains visible taggants
- Subfloor:** All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, lead, copper, brass, and polymeric poured floors; suspended wood
- Trowel:** S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; Regular notch (1/16" deep, 1/16" wide, 3/32" apart)
- Open Time:** Porous: Up to 10 minutes
Nonporous: 10-20 minutes
- Working Time:** Up to 25 minutes
- Spread Rate:** 145-170 sq. ft./gal.
(13-16 sq. m)
- Removal from Surface:** Use clean, white cloth.
Wet: neutral detergent and water;
Dry: mineral spirits
- Advantages:** Fast grab; Superior bond integrity; Moisture and alkali resistant; Solvent free; Freeze-thaw stable to 10°F (-12°C)
- Shelf Life:** One year if not opened
- Available Units:** Gal. (3.78 L), 4 Gal. (15.14 L)