

# S-599 Premium Commercial Vinyl Sheet Flooring Adhesive



## ▲ CAUTION

S-599 EYE AND SKIN IRRITANT

### INSTALLATION:

- Commercial Vinyl-Backed Flooring Installation System
- Commercial Inlaid Flooring Installation System
- Commercial Felt-Backed Installation System

### PRODUCTS:

- MEDINTECH
- ROYAL
- SOLID (Canadian Exclusive)
- MEDINTECH Tandem
- SAFEGUARD
- SAFEGUARD Spa
- TIMBERLINE
- TRANSLATIONS
- PERSPECTIVES Sheet and Tile
- POSSIBILITIES Petit Point
- Connection CORLON

### DESCRIPTION:

- Type:** Water-based/resin
- Color:** Creamy Beige; contains visible taggants
- Subfloor:** All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors and suspended wood
- Trowel:** S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart)
- Open Time:** Porous subfloors (set-in-wet): Minimum 10–20 minutes; nonporous subfloors (dry-to-touch): 30 minutes or more
- Working Time:** Up to one hour after dry to touch\*
- Spread Rate:** 250–300 sq. ft./gal. (23–28 sq. m)
- Removal from Surface:** Use clean white cloth  
Wet: neutral detergent and water; Dry: mineral spirits
- Advantages:** For Full Spread and Perimeter Plus Systems; Moisture and alkali resistant; Strong early grab
- Shelf Life:** One year if not opened
- Freeze/Thaw Stability:** Freeze-thaw stable
- Available Units:** Gal. (3.78 L), 4 Gal. (15.14 L)
- VOC Content:** <14 g/L; calculated and reported, SCAQMD 1168

\* Working times vary based on job conditions, subfloors, temperature and humidity.