

# S-599 Premium Vinyl-Back Flooring Adhesive



**CAUTION**

**S-599 EYE AND SKIN IRRITANT**

## INSTALLATION:

- Commercial Vinyl-Backed Flooring Installation System
- Luxury Solid-Vinyl Flooring Installation System
- Commercial Inlaid Flooring Installation System

## PRODUCTS:

- MEDINTECH
- ROYAL
- SAFEGUARD
- SAFEGUARD Design
- SAFEGUARD Hydro
- TIMBERLINE
- TRANSLATIONS
- PERSPECTIVES
- NATURAL CREATIONS
- NATURAL OPTIONS  
(All patterns except Rustico)
- POSSIBILITIES Petit Point
- Connection CORLON

## DESCRIPTION:

- Type:** Water-based/resin
- Color:** Creamy beige; contains visible taggants
- Subfloor:** All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors and suspended wood
- Trowel:** S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart)
- Open Time:** **Porous substrates (Set in wet):** Minimum 10–20 minutes; **Nonporous substrates (Dry to touch):** 30 minutes or more
- Working Time:** Up to one hour after dry to touch
- Spread Rate:** 250–300 sq. ft./gal. (23–28 sq. m)
- Removal from Surface:** Use clean white cloth  
Wet: neutral detergent and water; Dry: mineral spirits
- Advantages:** For Full Spread and Perimeter Plus Systems; Moisture and alkali resistant; Strong early grab; Freeze-thaw stable
- Shelf Life:** One year if not opened
- Available Units:** Gal. (3.78 L), 4 Gal. (15.14 L)