



SuperCoat™ Ceiling Panel Touch-up Paint

#5761 Ready-to-use formula provides superior coverage

- New, SuperCoat™... the best touch-up ceiling paint available
- Fast and easy to use for complete coverage
- Creates clean manufactured edge look on field cut panels
- New, large quart size, wide mouth can
- White latex smooth texture is great for use on mineral fiber and fiberglass ceiling panels



Where to Use:

Armstrong Touch-up Paint is intended to hide minor scratches and nicks in the surface and to cover field tegularized edges of mineral fiber and fiberglass ceiling tiles. Product has been formulated to compliment and coordinate with the finishes of these patterns. Not intended for refinishing panels. Stir before use.



Product Information/Physical Data:

See MSDS #15. Copies are available by calling 1 877 ARMSTRONG or checking our web site, armstrong.com/ceilings.

Irritant:

Avoid contact with eyes and skin. Wash thoroughly after handling. Do not take internally. Use only with adequate ventilation. Close container after use. First Aid: In case of eye contact, flush with plenty of water for at least 15 minutes. Get medical attention, if irritation results. If swallowed, get medical attention immediately. Keep out of reach of children. Read carefully complete Material Safety Data Sheet #15 for additional product information.

Disposal:

Use completely or absorb with inert material and dispose of container properly. Local disposal requirements vary. Consult your sanitation department or region's designated environmental protection agency for disposal options.

NOTE: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

Made in USA for Armstrong Building Products
Armstrong World Industries, Inc., Lancaster, PA 17604

