

► **BIOGUARD**



▲ Bioguard Plain



▲ Bioguard Perforated



Bioguard Plain Tegular






**BIOGUARD**

**BOARD**

**REGULAR**

**MICROLOOK**



**Bioguard Plain**

600 x 600 x 15 mm	2221 M	2223 M	2224 M
625 x 625 x 15 mm	2221 D	2223 D	2224 D
600 x 1200 x 15 mm	2222 M		
625 x 1250 x 15 mm	2222 D		

**Bioguard Perforated**

600 x 600 x 15 mm	2241 M	2243 M	2244 M
625 x 625 x 15 mm	2241 D	2243 D	2244 D
600 x 1200 x 15 mm	2242 M		
625 x 1250 x 15 mm	2242 D		



B + L	Klasse A1 (NBN S 21-203)
D	Klasse B1 (DIN 4102)
E	M0 (NPF 92-510)
F	M0 (NFP 92-510)
I	Classe 1 (D.M. 26/06/84)
NL	Klasse 2 (NEN 6065-6066)
RUS	Hard combustible (G1): GOST 303244-94; V1, D1, T1 NPB 244-97
PL	Niezapalny (PN-B-02874: 1996)
UK	Class 0/Class 1 (BS 476)



EN 20354 & EN 11654

Hz

$\alpha_w$	NRC	125	250	500	1000	2000	4000
<b>Bioguard Plain</b>							
<b>0.15(L)</b>	<b>0.15</b>	0.30	0.20	0.15	0.10	0.20	0.25
<b>Bioguard Perforated</b>							
<b>0.65</b>	<b>0.60</b>	0.35	0.45	0.60	0.75	0.70	0.60



EN 20140-9 & EN 717-1

**Dncw = 37 dB (Bioguard Plain)**

**Dncw = 34 dB (Bioguard Perforated)**



$\lambda = 0.052 - 0.057 \text{ W/m}^2\text{K}$



Bioguard Plain : 90 %  
Bioguard Perforated : 83 %



95 % RH



$\approx 4.6 \text{ kg/m}^2$

- Please contact our Internal Technical Sales Group for further details.
- Pour de plus amples informations merci de contacter notre Service Information Plafonds.
- Weitere Informationen erhalten Sie von unserem Kundenservice. Änderungen vorbehalten.
- Voor meer informatie kunt u contact opnemen met Market Service Center.
- Per ulteriori dettagli consultare il nostro Ufficio Commerciale.
- Para más detalles, por favor, contacte con el Servicio de Información de Techos.
- W razie dodatkowych pytań prosimy kontaktować się z biurem Armstrong w Warszawie

[www.armstrong-europe.com](http://www.armstrong-europe.com)