



V

Adhesives, Seam Treatments and Grout

V. Adhesives, Seam Treatments and Grout

A. WORK AREA PREPARATION

When applying adhesives, be sure to follow all instructions regarding the need for proper ventilation of the work area. Good work hygiene practices require careful review of all safety and health warnings and instructions contained in labels, specifications, instruction sheets, material safety data sheets, and other similar publications. See the Work Site Environment statement at the end of Chapter II.

B. ADHESIVE APPLICATION

Most flooring adhesives are applied with a notched trowel. The size of the notching is important because it controls the amount of adhesive applied. Notches that are too large spread too much adhesive. This can cause excessive indentations, trowel ridge show-through or bleeding at tile joints. Always check the adhesive label for the proper notching.

Substrates must be dry, clean, smooth, and free from paint, varnish, wax, oils, solvents, and other foreign matter. Dust and dirt on the subfloor will hamper the application and bonding of the new adhesive.

Check the amount of working time and open time for each adhesive. Open time is the amount of time recommended for the adhesive to set before it is covered with the flooring. Working time for tile is the amount of time from when the adhesive is set until the tile will no longer bond. Working time for sheet flooring is the amount of time from when the flooring is laid in place until all cutting and fitting is complete. When rolling is recommended, it must be completed within the working time of the adhesive. Both open time and working time are affected by temperature, humidity, and porosity of the subfloor.

There are two ways to fold the material back to spread the adhesive after the room has been fit: (1) lapping and (2) tubing. To lap the material, pull the material from the end of the sheet and spread the adhesive over one half of the room. Repeat the procedure for the other half of the room. To tube the material, pull the material back from the side of the sheet or tube it lengthwise. You may use both tubing and lapping on some installations.

Roll all sheet goods that are fully bonded with a 100-lb. roller immediately after placing them in the adhesive and again when the job is completed. Start in the center of the sheet and roll back and forth across the sheet to each end. Then reverse this procedure. Starting in the center of the sheet, roll lengthwise from center to edge. Rolling is a very important part of each installation. The bond is not as good if the material is not rolled down into the adhesive. Most Armstrong tile products do not require rolling.

C. ENVIRONMENTAL PRODUCT INFORMATION

Armstrong provides numerous products to help meet environmental criteria unique to adhesives and installation materials. You can use Armstrong adhesives with confidence, knowing that they have been formulated to provide the working characteristics your installers expect from Armstrong installation products.

Specific characteristics of each product are listed on the product label. The adhesives below all have the following characteristics:

- Low in VOCs (meet the requirements of SCAQMD Rule 1168)
- Nonflammable
- Ammonia-free and low odor
- Contain low or no organic solvents
- Contain no reportable hazardous substances (per current regulations)

This current list of installation products includes:

- S-235 Premium Sheet Flooring Adhesive
- S-254 Residential Sheet Flooring Adhesive
- S-288 Flooring Adhesive
- S-289 Flooring Adhesive
- S-580 Flash Cove Adhesive
- S-599 Premium Vinyl-Backed Flooring Adhesive
- S-700 Thin Spread Floor Tile Adhesive
- S-750 Premium Floor Tile Adhesive
- S-780 Linoleum Adhesive
- S-761 Seam Adhesive
- S-185 Latex Primer and Additive

S-135 VapArrest Professional Moisture Retardant System

⚠ CAUTION S-135 **EYE AND SKIN IRRITANT**

For use with the following Installation Systems:

- Laminate Flooring
- Fiberglass-Reinforced (Modified Loose Lay Method)
- ToughGuard II (Modified Loose Lay Method)
- Luxe Plank

DESCRIPTION:

Type:	Two-part cross-linked epoxy resin
Color:	Pale Red
Mixing:	Stir well before using. Using a power mixer, mix both components A & B in the pail containing part A (1/2" drill and paint or plaster paddle). Mix thoroughly for 2 minutes eliminating all color/clear streaks. Do not over mix.
Applicator:	Medium nap paint roller with extension handle
Spread Rate:	270 sq. ft. /gallon unit at 6 mil using a medium nap roller
Units:	Each unit (ctn) contains 1 part A & 1 part B Quart, 1.1 Gallon, 2.2 Gallon
Removal from Surface:	Remove wet or uncured materials with mineral spirits
Advantages:	Reduces water vapor transmission up to 75% (to less than 3 lbs./1000 sq. ft./24 hrs) Reduces potential for mold & mildew growth No additional prep time, easy to apply, rapid curing; ready to install next day Used over cementitious leveling compounds, environmentally friendly Low odor, no VOCs & low perm rating
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	Zero g/L; calculated and reported, SCAQMD 1168
Open Time:	8-24 hours when tack free
Working Time:	60 minutes (working times may vary based on job conditions, substrates, temperature, and humidity)
Substrates:	Concrete, properly mixed and applied Portland Cement-based underlayments, primed, properly prepared poured-in-place gypsum subfloors (dust free)

S-202 Static Dissipative Tile Adhesive

⚠ CAUTION S-202 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation System:

- Static Dissipative Tile (SDT)

DESCRIPTION:

Type:	Water-based resin
Color:	Black
Taggants:	None
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel with S-894 Fine Notch Blade Fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	Approximately 150 sq. ft. /gal. (14 sq. m)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Until dry to touch, 60 minutes or more
Working Time:	Up to 6 hours (working times may vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	6 months, unopened
Freeze/Thaw Stable:	No, keep from freezing
VOC Content:	< 50 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet or Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete and suspended wood Ceramic, terrazzo, polymeric poured, and certain metal subfloors when properly prepared with S-194 Radiant Heated subfloors where the surface temperature does not exceed 85° F (29° C)
Advantages:	Moisture and alkali resistant Long working time (up to 6 hours)

S-235 Residential Flooring Adhesive

⚠ CAUTION S-235 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Commercial Felt-Backed
- Residential Felt-Backed

DESCRIPTION:

Type:	Water-based rubber resin
Color:	Cream
Taggants:	Yes – 50% yellow and 50% orange
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel with S-893 Regular Notch or S-894 Fine Notch Blades Porous subfloors: Regular notch – (1/16" deep, 1/16" wide, 3/32" apart), U-notch Nonporous subfloors or existing resilient floors: Fine notch – (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	Regular notch: 125-150 sq. ft. /gal (12-14 sq. m.) Fine notch: 225-275 sq. ft. /gal (20-25 sq. m.)
Units:	1 quart (0.946 L); 1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Porous subfloors (wood, concrete) – 0 to 20 minutes Nonporous subfloors (existing flooring) – 10 to 20 minutes
Working Time:	Up to 40 minutes (working times may vary based on job conditions, substrates, temperature and humidity)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	4 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, lead, copper, brass, bronze, polymeric poured floors, and approved suspended wood Radiant heated subfloors where the surface temperature does not exceed 85° F (29°C)

Advantages:

Strong, fast initial grab (helps prevent edge curl)

Moisture and alkali resistant

Excellent bond integrity

Solvent-free and low odor



S-240 High Performance Epoxy Flooring Adhesive

⚠ CAUTION

S-240 **EYE AND SKIN IRRITANT
MAY CAUSE ALLERGIC SKIN OR RESPIRATORY REACTION
VAPOR HARMFUL
MIXING PART A AND PART B MAY GENERATE HEAT BUILD-UP**

For use with the following Installation Systems:

- Commercial Linoleum
- Vinyl Composition Tile (Safety Zone in Specialty Areas)
- Commercial Luxury Vinyl Tile
- Commercial Vinyl-Backed
- Commercial Inlaid
- Commercial Stair Tread and Rubber Tile

NOTICE – DO NOT USE AT TEMPERATURES ABOVE 85°F (29°C)

DESCRIPTION:

Type:	Two-part epoxy
Color:	Part A – Light Gray; Part B – Beige
Taggants:	None
Trowel:	S-891 Notched Steel Trowel – Fine notching S-892 Replaceable Blade Trowel with S-894 Fine Notch Blade Fine notch – (1/32" deep, 1/16" wide, 5/64" apart), U-notch For Rubber Tile S-891 Notched Steel Trowel – Regular notching S-892 Replaceable Blade Trowel with S-893 Regular Notch Blade Regular notch – (1/16" deep, 1/16" wide, 3/32" apart), U-notch Note: For linoleum and vinyl sheet products, trowel ridges must be rolled out using a 3/16" nap paint roller
Coverage:	170-190 sq. ft. /gallon (15-17 sq. m.)
Units:	1/2 gallon (1.89 L); 1 gallon (3.78 L) – Both are two-part units
Open Time:	Approximately 10-20 minutes (Set-in-wet)
Working Time:	Up to 1 hour (working times may vary based on job conditions, substrates, temperature and humidity)
Shelf Life:	2 years, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)

VOC Content:	Part A and Part B - 10 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, lead, polymeric poured floors, and approved suspended wood Radiant heated subfloors where the surface temperature does not exceed 85° F (29° C)
Advantages:	Moisture and alkali resistant Suitable for use with most Armstrong commercial installation systems

S-254 Residential Flooring Adhesive

⚠ CAUTION S-254 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation System:

- Residential Felt-Backed

DESCRIPTION:

Type:	Water-based rubber resin
Color:	Tan
Taggants:	Yes – 50% yellow and 50% orange
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel with S-893 Regular Notch or S-894 Fine Notch Blades Porous subfloors: Regular notch – (1/16" deep, 1/16" wide, 3/32" apart), U-notch Nonporous subfloors or existing resilient floors: Fine notch – (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	Regular notch: 125-150 sq. ft. /gal (12-14 sq. m.) – 14-17 sq. yd. /gal Fine notch: 225-275 sq. ft. /gal (20-25 sq. m.) – 25-31 sq. yd. /gal
Units:	1 quart (0.946 L); 1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Porous subfloors – 0 to 20 minutes Nonporous subfloors – 10 to 20 minutes
Working Time:	Up to 20 minutes over concrete; up to 60 minutes over wood and other substrates (working times may vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	5 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits

Subfloors: All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors, and suspended wood; primed, poured-in-place gypsum subfloors

Radiant heated subfloors where the surface temperature does not exceed 85° F (29° C)

Advantages: For Full Spread and Perimeter Plus systems

Moisture and alkali resistant

Strong, early grab

Nonflammable, ammonia-free and low odor

Contains low or no organic solvents

S-288 Premium Vinyl Sheet Flooring Adhesive

⚠ CAUTION S-288 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Fiberglass-Reinforced Sheet Flooring
- ToughGuard II
- Alterna
- Residential LVT Planks
- Commercial Luxury Vinyl Tile Flooring

DESCRIPTION:

Type:	Water-based rubber resin
Color:	Creamy beige
Taggants:	Yes – green glitter
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; Fine notch – (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	250-300 sq. ft. /gallon (23-28 sq. m.)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Porous substrates – Set-in-wet: Minimum 10-20 minutes Nonporous substrates – Dry-to-touch: 30 minutes or more
Working Time:	Up to 1 hour (working times may vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	2 years, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	< 14 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors, and suspended wood

Advantages:

For Full Spread Installation Systems

Moisture and alkali resistant

Strong, early grab

Armstrong Guaranteed Installation System (AGIS)
Guarantee included as part of Armstrong Installation
System when installing Armstrong vinyl-back sheet
flooring and residential Luxury Vinyl Tile

Nonflammable, ammonia-free and low odor; contains low
or no organic solvents

Contains no reportable hazardous substance (per current
regulations)

S-289 Releasable Flooring Adhesive

⚠ CAUTION S-289 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Fiberglass Reinforced Sheet
- Residential LVT Planks
- ToughGuard II

DESCRIPTION:

Type:	Water-based rubber resin
Color:	Creamy beige
Taggants:	Yes – 50% yellow and 50% orange
Paint Roller:	Smooth, 1/4" nap paint roller
Trowel (permanent):	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	275-325 sq. ft. (30-36 sq. yds.)/gal (25-30 sq. m.) (paint roll) 250-300 sq. ft. /gal (23-28 sq. m.) (trowel)
Units:	1 gallon (3.78 L), 4 gallons/ctn.; weight (38 lbs./ctn.) (17.2 kg./ctn.); 45 ctns. / pallet 4 gallon (15.14 L), 1 pail, weight (37.5 lbs.) (17 kg.); 48 pails / pallet
Open Time:	For all approved subfloors Allow the adhesive to set open until dry-to-touch, approximately 45 to 60 minutes; the adhesive should be tacky with no transfer to fingers
Working Time:	Unlimited
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	11 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors, and suspended wood

Advantages:

Moisture and alkali resistant

Fast application with roller

Easy to repair and remove

AGIS Guarantee

Nonflammable, ammonia-free and low odor

Contains low or no organic solvents

S-515 Clear Thin Spread Tile Adhesive

⚠ CAUTION S-515 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation System:

- Vinyl Composition Tile

DESCRIPTION:

Type:	Water-based/latex resin
Color:	Cream; contains visible taggants
Taggants:	Yes – 50% yellow and 50% orange
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	350-400 sq. ft. /gal (33-37 sq m.)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Dry-to-touch: 30 minutes or more
Working Time:	Up to 24 hours (working times may vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	Zero g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	Concrete on all grade levels. Existing asphalt “cutback” residue that is smooth with no ridges or puddles evident. Suspended wood and wood underlayments. Existing well-bonded resilient flooring. Not perimeter-bonded or cushion-backed. Ceramic tile, terrazzo, marble, and polymeric-poured floors. Properly mixed and applied powder underlayment and embossing levelers. Primed, poured-in-place gypsum subfloors. Radiant-heated subfloors where the surface temperature does not exceed 85° F (29° C).

Advantages:

24-hour working time

Dries clear (allows chalk lines to show through)

Excellent initial grab

Moisture and alkali resistant

Suitable for use with VCT and Safety Zone over high moisture concrete slabs

Can be used over “cutback” adhesive residue

S-525 Clear Thin Spread BioBased Tile Adhesive

⚠ CAUTION S-525 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Vinyl Composition Tile
- BioBased Tile

DESCRIPTION:

Type:	Water-based/latex
Color:	Beige; dries clear
Taggants:	None
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	275-325 sq. ft. /gal (25.5-30.2 sq. m. / 3.78 L)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Dry-to-touch: 20 minutes or more
Working Time:	Up to 24 hours (working times may vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	2 years, unopened
Freeze/Thaw Stable:	Yes, to 20° F (-7° C)
VOC Content:	16 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	Concrete on all grade levels. Existing asphalt “cutback” residue that is smooth with no ridges or puddles evident. Suspended wood and wood underlayments. Existing well-bonded resilient flooring; not perimeter-bonded or cushion-backed. Ceramic tile, terrazzo, marble, and polymeric-poured floors. Properly mixed and applied powder underlayment and embossing levelers. Primed, poured-in-place gypsum subfloors. Radiant-heated subfloors where the surface temperature does not exceed 85° F (29° C).

Advantages:

24-hour working time

Dries clear

Excellent initial grab

Moisture and alkali resistant

Suitable for use with VCT, BioBased Tile, and Safety Zone over high moisture concrete slabs

Can be used over “cutback” adhesive residue (reduces subfloor preparation time) except when installing VCT or Safety Zone over high moisture slabs

One step installation, no primer required

S-543 Premium Plus Commercial Vinyl Sheet Flooring Adhesive

⚠ CAUTION S-543 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Commercial Vinyl-Backed
- Commercial Heterogeneous and Inlaid
- Commercial Felt-Backed
- Commercial Luxury Vinyl Tile
- Residential LVT Plank

DESCRIPTION:

Type:	Water-based/synthetic polymer
Color:	White; contains visible taggants
Taggants:	50% Yellow and 50% Orange
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	225-275 sq. ft. (25-30 sq. yds.) /gal (21-26 sq. m.)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Porous substrates – Set-in-wet: Minimum 10-20 minutes Nonporous substrates – Dry-to-touch: 30 minutes or more
Working Time:	Up to 8 hours (working times may vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	Zero g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors, and suspended wood

Advantages:

Increased working time

High bond strength

Can be used in all commercial vinyl-backed sheet flooring applications

Strong initial grab for “set-in-wet” sheet installations

Superior moisture and alkali resistance

Anti-fungal/mold protection



S-580 Flash Cove Adhesive

⚠ CAUTION S-580 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Commercial Vinyl-Backed
- Commercial Heterogeneous and Inlaid
- Commercial and Residential Felt-Backed
- Commercial/Residential Linoleum Sheet
- Fiberglass-Reinforced Sheet (Full spread application)
- ToughGuard II

DESCRIPTION:

Type:	Water-based/resin; pressure-sensitive; acrylic base
Color:	White
Taggants:	Contains no visible taggants
Applicator:	Brush or roller
Coverage:	200–250 sq. ft./ half-gallon (18-23 sq. m.)
Units:	Half-gallon (1.89 L)
Open Time:	Dry to pressure sensitive state; minimum of 20-30 minutes
Working Time:	Unlimited (working times may vary based on job conditions, temperature, humidity, air circulation, etc.)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	Zero g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Walls:	Standard, structurally sound
Advantages:	Moisture and alkali resistant Excellent grab AGIS Guarantee Nonflammable, ammonia-free and low odor Contains low or no organic solvents

S-599 Premium Commercial Vinyl Sheet Flooring Adhesive

⚠ CAUTION S-599 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Commercial Vinyl-Backed
- Commercial Heterogeneous and Inlaid
- Commercial Felt-Backed

DESCRIPTION:

Type:	Water-based resin
Color:	Creamy beige
Taggants:	Yes – blue glitter
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	250–300 sq. ft./gallon (23-28 sq. m.)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Porous substrates – Set-in-wet: Minimum 10-20 minutes Nonporous substrates – Dry-to-touch: 30 minutes or more
Working Time:	Up to 1 hour (working times may vary based on job conditions, temperature, humidity, air circulation, etc.)
Shelf Life:	2 years, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	< 14 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors and suspended wood Radiant Heated subfloors where the surface temperature does not exceed 85° F (29° C)

Advantages:

For Full Spread and Perimeter Plus systems

Moisture and alkali resistant

Strong, early grab

AGIS Guarantee

Nonflammable, ammonia-free, and low odor

Contains low or no organic solvents

S-693 Premixed Sanded Acrylic Grout

⚠ CAUTION S-693 EYE AND SKIN IRRITANT

For use with the following Installation System:

- Groutable tile installation systems

DESCRIPTION:

Type:	Premixed sanded acrylic grout
Color:	Available in a variety of colors
Taggants:	None
Float:	Hard epoxy
Coverage:	350 sq. ft./gal. (32 sq. m.) with 1/16" joint spacing 325 sq. ft./gal. (30 sq. m.) with 1/8" joint spacing 275 sq. ft./gal. (25 sq. m.) with 3/16" joint spacing 225 sq. ft./gal. (21 sq. m.) with 1/4" joint spacing
Units:	1 gallon (3.78 L)
Open Time:	Approximately 3 to 8 minutes
Working Time:	Up to 10 minutes (working times may vary based on job site conditions, substrates, temperature, and humidity)
Shelf Life:	2 years, unopened
Freeze/Thaw Stable:	No, keep from freezing
VOC Content:	15 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Use clear cool water and a sponge. Do not allow grout to dry on face.
Advantages:	Premixed-ready to use Resists cracking Color consistent Stain resistant Easy clean up

S-700 Thin Spread Floor Tile Adhesive

⚠ CAUTION S-700 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Vinyl Composition Tile
- BioBased Tile

DESCRIPTION:

Type:	Water-based/asphalt-rubber
Color:	Black
Taggants:	Contains no visible taggants
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	350–400 sq. ft./gallon (32-37 sq. m.)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Until dry to touch; approximately 30 minutes or more
Working Time:	18 hours (working times may vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	Zero g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, ceramic, terrazzo and marble. Polymeric poured floors, suspended wood, and wood underlayments. Steel, stainless steel, aluminum, lead, copper, brass, and bronze. Properly mixed and applied powdered underlayment. Primed and poured-in-place gypsum subfloors. Radiant-heated subfloors where the surface temperature does not exceed 85° F (29° C).
Advantages:	Moisture and alkali resistant AGIS Guarantee Nonflammable, ammonia-free, and low odor Contains low or no organic solvents Can be used over “cutback” adhesive residue (reduces subfloor prep)

S-725 Wall Base Adhesive

⚠ CAUTION S-725 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation System:

- WALL BASE, RISERS, and Vinyl TRANSITION STRIPS

DESCRIPTION:

Type:	Water-based/rubber-resin
Color:	Off-white
Taggants:	Yes – 50% yellow and 50% orange
Trowel:	1/16" deep, 1/16" wide, 3/32" apart), U-notch
Coverage:	2-1/2" WALL BASE: 375-425 lin. ft./gal (114-130 m. lin.) 4" WALL BASE: 300-350 lin. ft./gal (91-107 m. lin.) 6" WALL BASE: 200-250 lin. ft./gal (61-76 m. lin.) 7" RISER: 200-250 lin. ft./gal (61-76 m. lin.) 11-oz cartridge – 4": 1/8" bead – 18 lin. ft. (5.5 m. lin.) 30-oz cartridge – 4": 1/8" bead – 50 lin. ft. (15.2 m. lin.)
Units:	11-oz cartridge (311.8 grams) 30-oz cartridge (950.4 grams) quart (946 ml) gallon (3.78 L) 4 gallons (15.14 L)
Open Time:	None recommended
Working Time:	Up to 15 minutes
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	Zero g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Walls:	Structurally sound and dry wall surfaces

Advantages:

Moisture and alkali resistant

Good wet strength

Excellent bond integrity

Versatile (use for rubber or vinyl WALL BASE)

AGIS Guarantee

Nonflammable

S-750 Premium Tile Flooring Adhesive

⚠ CAUTION S-750 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Commercial Vinyl Composition Tile
- Residential Dry Back Vinyl Tile
- Primer for wood and concrete with self-adhering tile

DESCRIPTION:

Type:	Water-based/rubber resin
Color:	Cream
Taggants:	Yes – 50% yellow and 50% orange
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch To apply as a primer, use a brush or medium-nap roller
Coverage:	275–350 sq. ft. /gallon (26-33 sq. m.) Brush or roller (Primer): 350–400 sq. ft./gallon (33-37 sq. m.)
Units:	1 quart (946 mL), 1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Until dry-to-touch: approximately 30 minutes or more
Working Time:	Up to 6 hours (working times may vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	No, keep from freezing
VOC Content:	5 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, polymeric poured floors, and suspended wood
Advantages:	Can be used over “cutback” adhesive residue Moisture and alkali resistant Strong, early grab AGIS Guarantee Nonflammable, ammonia-free and low odor Contains low or no organic solvents

S-761 Seam Adhesive

⚠ CAUTION S-761 **EYE AND SKIN IRRITANT**

For use with the following Installation Systems:

Highly Recommended:

- Residential Linoleum

Optional:

- Commercial Linoleum
- Commercial Vinyl-Backed
- Commercial Felt-Backed
- Commercial Heterogeneous and Inlaid
- Full-Spread Light Commercial Glass Back
- Fiberglass-Reinforced Sheet Flooring
- Residential Felt-Backed
- ToughGuard II

DESCRIPTION:

Type:	Water-based/ resin
Color:	White
Taggants:	Yes – saturn yellow
Coverage:	1/8" bead, approximately 144 lin. ft./bottle (43 lin. m.)
Units:	8 oz. (236 mL) bottle; 12/ctn.
Open Time:	None recommended
Working Time:	15 minutes
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	No, keep from freezing
VOC Content:	136 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	Nonflammable, ammonia-free and low odor Contains low or no organic solvents

S-780 Linoleum Adhesive

⚠ CAUTION S-780 **EYE AND SKIN IRRITANT**

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Commercial Linoleum
- Residential Linoleum

DESCRIPTION:

Type:	Synthetic Polymer
Color:	White
Taggants:	Yes – 50% yellow and 50% orange
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; regular notch (1/16" deep, 1/16" wide, 3/32" apart), U-notch
Coverage:	120-135 sq. ft./gallon (11-12.5 sq. m.)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Porous substrates – Set-in-wet: No open time Nonporous substrates – 5-10 minutes
Working Time:	Up to 25 minutes (working times may vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10°F (-12° C)
VOC Content:	5.5 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors, and suspended wood
Advantages:	Moisture and alkali resistant Can be installed over concrete slabs with high moisture Strong, early grab AGIS Guarantee Nonflammable, ammonia-free and low odor Contain low or no organic solvents

Bruce EverSeal Adhesive

⚠ CAUTION EVERSEAL **EYE AND SKIN IRRITANT**

For use with the following Installation Systems:

- Residential Laminate Flooring
- Light Commercial Laminate Flooring

DESCRIPTION:

Type:	Polyvinyl acetate cross-linking emulsion (water-based)
Color:	White when wet; dries opaque in 1 hour; contains no visible taggants
Taggants:	None
Applicator:	Predrilled cap on 16 oz. bottle
Spread Rate:	3/32" (2.4 mm) bead up to 150 sq. ft. (500 lin. ft.)/ 16 oz. bottle
Units:	16 oz. bottle (473 ml); 12 bottles/ ctn.; weight 14.4 lb./ ctn.
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Keep from freezing
VOC Content:	25 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet: clean, white cloth dampened with warm water. Dry: can be easily peeled away; remove residue/haze with cloth dampened 8 oz. (1 cup) white distilled vinegar to 1 gal. water (1:16 ratio)
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors, and suspended wood
Advantages:	Nonflammable Easy clean up Designed to create a strong water resistant bond between tongue and groove; use for laminate installations full bathrooms, high moisture areas, and light commercial environments

Armstrong 99 Adhesive

⚠ CAUTION

99

EYE AND SKIN IRRITANT

For use with the following Installation Systems:

- Residential Laminate Flooring
- Light Commercial Laminate Flooring

DESCRIPTION:

Type:	Polyvinyl acetate cross-linking emulsion (water-based)
Color:	White when wet; dries opaque in 1 hour; contains no visible taggants
Taggants:	None
Applicator:	Predrilled cap on 16 oz. bottle
Spread Rate:	3/32" (2.4 mm) bead up to 150 sq. ft. (500 lin. ft.)/ 16 oz. bottle
Units:	16 oz. bottle (473 ml); 12 bottles/ ctn.; weight 14.4 lb./ ctn.
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Keep from freezing
VOC Content:	25 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet: clean, white cloth dampened with warm water. Dry: can be easily peeled away; remove residue/haze with cloth dampened 8 oz. (1 cup) white distilled vinegar to 1 gal. water (1:16 ratio)
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors, and suspended wood
Advantages:	Nonflammable Easy clean up Designed to create a strong water resistant bond between tongue and groove; use for laminate installations full bathrooms, high moisture areas, and light commercial environments

