

PAINTED NUBBY Open Plan

Tegular
fine texture

Relative Installed Cost

\$	\$\$	\$\$\$	\$\$\$\$
----	------	--------	----------



Key Selection Attributes

- Outstanding acoustical performance; Superior Articulation Class (190-200) and NRC (up to 0.95)
- Humidity-resistant **HumiGuard Plus** performance to inhibit panel sag




- High light reflectance
- Fine texture coordinates with CIRRUS Ceilings
- 10-year limited warranty; 15-year with **HumiGuard Plus** products and Armstrong hot dipped galvanized grid

Typical Applications

- Open plan offices
- Gymnasiums and auditoriums
- Areas requiring superior acoustics, sag resistance and energy efficiency

Recycled Content:
25%
(Recycled Glass)

Color



Visual Selection

Performance Selection

GRID FACE	EDGE PROFILE	ITEM NUMBER	DIMENSIONS	UL Classified ACOUSTICS	FIRE	SAG RESIST	LIGHT * REFLECT	DURABILITY	
									NRC
PAINTED NUBBY Open Plan Tegular									
9/16"	Square Tegular	3201	24 x 24 x 1"	[Icon]	0.95 190	37*	Class A	0.84	Standard
		3201M	600 x 600 x 25mm						
9/16"	Square Tegular	79012**	24 x 24 x 1"	[Icon]	0.90 200	24	Class A	0.84	Standard
		79012M**	600 x 600 x 25mm						
15/16"	Square Tegular	3200	24 x 24 x 1"	[Icon]	0.95 190	37*	Class A	0.84	Standard
		3200M	600 x 600 x 25mm						
15/16"	Square Tegular	79011**	24 x 24 x 1"	[Icon]	0.90 200	24	Class A	0.84	Standard
		79011M**	600 x 600 x 25mm						

* With optional field installed 5/8" mineral fiber backing, internally tested only
 ** CAC Backing
 ★ Light reflectance values shown as averages



Physical Data

Material

Moisture-resistant and dimensionally stable woven glass fibers adhered to fiberglass board
 79011, 79012 – CAC Backing

Surface Finish

Factory-applied latex paint

Fire Performance

Class A: Flame Spread 25 or under (UL Labeled) per ASTM E 1264

ASTM E 1264 Classification

Type XII, Form 2, Pattern E

Insulation Value

3200, 3201, 79011, 79012 – R Factor – 4.0 (BTU units)
 R Factor – 0.70 (Watts units)

Backloading Recommendation

Contact TechLine for specific information

Weight; Square Feet/Carton

0.50 lbs/SF; 96 SF/ctn

Warranty

See Warranty Information at armstrong.com/ceilingswarranty.

Recommended Suspension System

ITEMS	SUSPENSION SYSTEM
3200, 79011	15/16" PRELUDE
3201, 79012	9/16" SUPRAFINE 9/16" SONATA 9/16" INTERLUDE 9/16" SILHOUETTE Bolt-Slot 9/16" TRIMLOK Screw-Slot

special performance

Fiberglass