# CALLA® Health Zone™

## Square Lay-in & Tegular
## smooth texture

TOTAL ACOUSTICS®
Sound Absorption (NRC)
+ Sound Blocking (CAC)

SUSTAIN®
High Performance
Sustainable
Ceiling Systems

CAD/Revit® drawings at:
armstrong.com/cadrevit



Calla Health Zone Square Tegular panels with Suprafine® 9/16" suspension system





Perfect for office, education, and healthcare spaces

**Smoothest mineral fiber ceiling available; combines exceptional acoustical performance, sustainability, and functionality attributes in one go anywhere ceiling panel that is especially durable and aesthetically pleasing for every healthy space.**

### KEY SELECTION ATTRIBUTES


- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Meets or exceeds USDA/FSIS, FGI, HIPAA and ANSI S12.60 guidelines
- Anti-Bacterial/Mold/Mildew – BioBlock® Plus performance resists the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface
- Exceptional durability & cleanability with a smooth, durable finish – impact-, scratch-, and soil-resistant
- CleanAssure™ – safe for use with disinfectant cleaners
- Calla® Health Zone™ panels are part of the Sustain® portfolio and meet the most stringent sustainability compliance standards today
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant
- Clean Room Performance up to ISO Class 5 (Class 100) using gasketed Clean Room™ suspension systems
- Energy-saving, high light-reflective finish
- 30-Year Limited System Warranty against visible sag, mold, mildew, and bacterial growth
- 10-Year replacement panel available for items 2230, 2233, 2231, 2234, 2232, 2235

10-YEAR REPLACEMENT PANEL AVAILABILITY

### TYPICAL APPLICATIONS

- Education
- Office
- Kitchen / Food prep areas
- Healthcare
  - Patient rooms
  - Treatment rooms
  - Nurses' stations
  - Emergency rooms
  - Restrooms
  - Clean Rooms

### COLORS



White (WH) | Black (BK) | Stone (SE) | Custom Colors Available*

* Standard colors are pre-qualified to meet Sustain® portfolio requirements. Custom colors may need to be evaluated if sustainability criteria is required.

### DETAILS



1. Calla® Health Zone™ Square Lay-in
2. Calla® Health Zone™ Square Tegular
3. Calla Health Zone Square Tegular with Suprafine® 9/16" suspension system

TechLine 877 276-7876
armstrong.com/healthzone

Armstrong® World Industries

# CALLA® Health Zone™

## Square Lay-in & Tegular
smooth texture

USDA CERTIFIED BIOBASED PRODUCT
PRODUCT 91%

SUSTAIN® High Performance Sustainable Ceiling Systems

Declare®

RECYCLED CONTENT
UP TO 85%

LEED V5 — Ecomedes Data

COMMON MATERIALS FRAMEWORK

| | | | |
|---|---|---|---|
| Human Health | Declare Label | Climate Health | EPD |
| | HPD | Ecosystem Health | EPD |
| | 3rd Party CDPH | Circular Economy | ✓ |
| OCCUPANT EXPERIENCE | | Acoustics | ✓ |

## VISUAL SELECTION

## PERFORMANCE SELECTION
Dots represent high level of performance. $$$$

| | Item No. | Dimensions (Inches) | | UL Classified Acoustics NRC | + CAC | = | Total Acoustics[1] NRC + CAC | Fire Performance | Light Reflect* | Bio-Block+ Anti-Bacterial/ Mold/ Mildew | Humi-Guard+ Sag Resistant | Certified Low VOC Emissions | CleanAssure™ Disinfectable Panels: Fog & Spray | Wipe | Water Repel | DURABILITY: Wash* | Scrub* | Impact | Scratch* | Soil | Recycle Program | 30-Yr Warranty |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| CALLA® Health Zone™ 15/16" Square Lay-in | 2230 | 24 × 24 × 1" | | 0.80 | 38 | | BEST | Class A | 0.85 | + | • | • | • | • | • | • | • | • | • | • | • | • |
| | 2233 | 24 × 48 × 1" | | 0.80 | 38 | | BEST | Class A | 0.85 | + | • | • | • | • | • | • | • | • | • | • | • | • |
| | 2236 | 30 × 30 × 1" | | 0.80 | 38 | | BEST | Class A | 0.85 | + | • | • | • | • | • | • | • | • | • | • | • | • |
| 15/16" Square Tegular | 2231 | 24 × 24 × 1" | | 0.80 | 38 | | BEST | Class A | 0.85 | + | • | • | • | • | • | • | • | • | • | • | • | • |
| | 2234 | 24 × 48 × 1" | | 0.80 | 38 | | BEST | Class A | 0.85 | + | • | • | • | • | • | • | • | • | • | • | • | • |
| | 2237 | 30 × 30 × 1" | | 0.80 | 38 | | BEST | Class A | 0.85 | + | • | • | • | • | • | • | • | • | • | • | • | • |
| 9/16" Square Tegular | 2232 | 24 × 24 × 1" | | 0.80 | 38 | | BEST | Class A | 0.85 | + | • | • | • | • | • | • | • | • | • | • | • | • |
| | new 2232BK | 24 × 24 × 1" | | 0.80 | 38 | | BEST | Class A | N/A | + | • | • | • | • | • | • | • | • | • | • | • | • |
| | new 2232SE | 24 × 24 × 1" | | 0.80 | 38 | | BEST | Class A | N/A | + | • | • | • | • | • | • | • | • | • | • | • | • |
| | 2235 | 24 × 48 × 1" | | 0.80 | 38 | | BEST | Class A | 0.85 | + | • | • | • | • | • | • | • | • | • | • | • | • |
| | 2238 | 30 × 30 × 1" | | 0.80 | 38 | | BEST | Class A | 0.85 | + | • | • | • | • | • | • | • | • | • | • | • | • |
| | | 1" Thick – 15/16" Square Lay-in & 15/16" & 9/16" Square Tegular | | | | | | | | | | | | | | | | | | | | |
| Made-to-Order Sizes | | | | N/A | N/A | | N/A | Class A | 0.85 | + | • | • | • | • | • | • | • | • | • | • | • | • |


4-6 WEEKS order to ship

Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrong.com

| Width | Length |
|---|---|
| 4" – 1-1/2" | 12" – 72" |
| 12" – 30" | 4" – 72" |
| 30-1/2" – 48" | 4" – 24" |

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
**GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)
* Advertised values for light reflectance, wash, scrub and scratch resistance are applicable to White panels only

## SUSPENSION SYSTEMS
*CAC 29 achieved with Clean Room™ suspension system; not UL® Classified for acoustics.




Prelude®
Co-Extruded Clean Room™ (Steel or Aluminum)
Co-Extruded Clean Room (Steel or Aluminum)
Silhouette® 1/4" Reveal
Silhouette 1/8" Reveal
Suprafine®
Interlude® XL® HRC

NOTE: Clean Room Class 5 (Class 100) (item 2231) UL Classified for Acoustics on 15/16" suspension system only.

## PHYSICAL DATA

**Material**
Wet-formed mineral fiber with acoustically transparent membrane

**Surface Finish**
Acoustically transparent membrane with factory-applied latex paint

**Fire Performance**
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

**ASTM E1264 Classification**
Type A, Form A2.2, Pattern G; Fire Class A

**Humidity/Sag Resistance**
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Bacterial/Mold/Mildew**
Ceiling tiles with BioBlock® Plus performance resist the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface.

**VOC Emissions**
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**High Recycled Content**
Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Insulation Value**
R Factor – 2.9 (BTU units)
R Factor – 0.445 (Watts units)

**Cleaning and Disinfecting**
Cleaning and CDC-recommended disinfecting options available on armstrong.com/cleaning

Only white panels are washable and scrubbable.

**Design Considerations**
Physical product samples for standard and custom colors are available upon request. Please refer to the physical product sample prior to making a final selection. While we strive to ensure exact color matches, various factors such as differences in materials, texture, substrate porosity, painting processes, lighting, and observer subjectivity can all affect how paint colors appear on ceiling and wall panels, suspension systems, and trim products. Due to these and other differences, ceiling and wall panels, trim products, and suspension systems with the same color name will coordinate but may not be an exact color match. Product is dye-lotted. Order sufficient initial quantities and attic stock to minimize possible color variation.

**30-Year Performance Guarantee & Warranty**
When installed with Armstrong® Suspension System. Details at armstrong.com/warranty

**Weight; Square Feet/Carton**
2230, 2231, 2232, 2232BK, 2232SE – 1.0 LBS/SF; 40 SF/CTN
2233, 2234, 2235 – 1.0 LBS/SF; 48 SF/CTN
2236, 2237, 2238 – 1.0 LBS/SF; 50 SF/CTN

**Minimum Order Quantity**
1 carton


TechLine / 877 276-7876
armstrong.com/healthzone



BPCS-6028-1026



LEED® is a trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are trademarks of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2026 AWI Licensing LLC


Armstrong® World Industries

MINERAL FIBER – Standard