CREATE™
ULTIMA®, ULTIMA® Health Zone™, OPTIMA®

Square Lay-in, Tegular & Vector®
fine texture

TOTAL ACOUSTICS®
Sound Absorption (NRC)
+ Sound Blocking (CAC)









plus capabilities to do more



Ultima Create! Vector panels with Prelude XL 15/16" suspension system

armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Create your own custom design on smooth-texture panels, including Ultima®, Ultima® Health Zone™, or Optima® panels without detriment to Total Acoustics® panel performance. Great acoustics have never been so colorful.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Your unique visuals set the stage for a themed environment
- Flexibility to adapt different performance across lines, including Ultima, Ultima Health Zone and Optima
- Excellent options for sound absorption – NRC 0.70 – 0.90
- Mold- and mildew-resistant surface
- Product is directional
- Custom samples available
- Can contribute to LEED® credits
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

CREATE YOUR OWN UNIQUE, CUSTOM CEILING VISUAL USING ARTWORK

Original Artwork Guidelines:

- Artwork must be vector-based
- Acceptable file types:
  - Adobe® Illustrator® – .ai
  - Encapsulated PostScript – .eps
  - Scalable Vector Graphics – .svg
- Acceptable Color Mode: CMYK

Original Digital Image Requirements:

- Image must be 150 dpi at full print size
- Acceptable file types:
  - Joint Photographic Experts Group – .jpg
  - Tagged Image File Format – .tiff

NOTE: Create! panels are intended for printed visuals only. Looking for solid colors? Choose Calla® or Lyra® ceiling panels.

TechLine 877 276-7876
armstrongceilings.com/create

Armstrong® World Industries

CREATE™
ULTIMA®, ULTIMA® Health Zone™, OPTIMA®

Square Lay-in, Tegular & Vector®
fine texture

SUSPENSION SYSTEM AND TRIM COLORS

Due to printing limitations, shade may vary from actual product.

White (WH)
Black (BL)
Silver Grey (SG)
Gun Metal Grey (MY)
Silver Satin (SA)
Ivory (IV)
Medium Taupe (MT)
Adobe (AD)
Light Grey (LG)
Grey Stone (GS)
Basalt (SBT)
Riverstone (SRV)
Custom Colors Available*

Coffee (SCE)
Polar (SPO)
Limestone (SLM)
Fossil (SFL)
Sandstone (SSS)
Hay (SHY)
Oat (SOT)
Mist (SMT)
Pacific (SPC)
Rainstorm (SRS)
Lilac (SLC)
Twilight (STT)

Ocean (SOC)
Boxwood (SBW)
Fern (SFN)
Ivy (SIV)
Feldspar (SFS)
Topaz (STZ)
Bronzite (SBZ)
Honeysuckle (SHS)
Marigold (SMG)
Rose (SRO)

* Colors that are pre-qualified to meet Sustain™ portfolio requirements are available upon request. Other made-to-order colors must be evaluated if sustainability criteria is required. Lead time will increase.

Powder-coated Finishes

Blizzard White (ZW)
Charcoal Black (ZB)

NOTE: Powder-coated finishes are also available on select Axiom® Classic, Knife Edge®, and Vector® trim profiles

NOTE: 360° paint finishes and custom colors available as special order. Visit armstrongceilings.com/natureinspired to get information about coordinated Armstrong colors.

THEMES – Available on ULTIMA®, ULTIMA® Health Zone™, OPTIMA® CREATE!™ Panels

Blooms



Single Panel
Design 021



4-Panel Design
Design 022 (Add A, B, C, or D for individual panel order)

Dragonflies



Single Panel
Design 051



4-Panel Design
Design 052 (Add A, B, C, or D for individual panel order)

Stars



Single Panel
Design 041



Single Panel
Design 042



Single Panel
Design 043

Bubbles

Single Panel
Design 011



Single Panel
Design 012



Single Panel
Design 013

CALL, DON'T FALL – Available on Ultima Health Zone Create! Square Lay-in Panels

Reinforce safety in patient rooms by printing warning messages, in any language, on ceiling panels. Custom designs are also available.



Custom Designs for Create!™ ceilings

NOTE: Replacement panels may vary slightly in color due to material variations over time. Product could have slight color variation from run to run; adequate attic stock should be ordered.



Optima® Create!™ Vector® panels with Prelude® XL® suspension system



Ultima® Create!™ Vector® panels with Prelude® XL® suspension system



Ultima® Create!™ Custom panels with Prelude® XL® suspension system



Ultima® Create!™ Custom panels with Prelude® XL® suspension system

TechLine 877 276-7876
armstrongceilings.com/create

Armstrong® World Industries

MINERAL FIBER & FIBERGLASS – Standard

CREATE™
ULTIMA®, ULTIMA® Health Zone™, OPTIMA®

Square Lay-in, Tegular & Vector®
fine texture

LEED V5 Refer to individual product pages for LEED info.

MINERAL FIBER – Standard

VISUAL SELECTION

PERFORMANCE SELECTION


Dots represent high level of performance. $$$$

	Item No.	Dimensions (Inches)		UL Classified Acoustics NRC	+ CAC	= Total Acoustics[1] NRC + CAC	Fire Performance	Bio-Block Anti-Mold/ Mildew	Humi-Guard+ Sag Resistant	DURABILITY Water Repel	DURABILITY Soil	Recycled Content	Recycle Program	30-Yr Warranty
ULTIMA® or OPTIMA® CREATE!™ Square Lay-in for 15/16" Prelude® XL®	Z1910UC1 (Ultima)	24 × 24 × 3/4"	☐	0.75 •	35 •	BETTER	Class A	•	•	N/A	•	•	•	•
	Z33520C1 (Optima)	24 × 24 × 1"	☐	0.90 •	26	N/A	Class A	•	•	N/A	•	•	N/A	•
ULTIMA® CREATE!™ Tegular for 9/16" Silhouette® XL® ONLY; 1/4" or 1/8" Reveal	Z1912UC1	24 × 24 × 3/4"	☐	0.75 •	35 •	BETTER	Class A	•	•	N/A	•	•	•	•
ULTIMA® or OPTIMA® CREATE!™ Vector® for 15/16" Prelude XL (White only)	Z1920UC1 (Ultima)	24 × 24 × 3/4"	☐	0.70 •	33	N/A	Class A	•	•	N/A	•	•	•	•
	Z39010C1 (Optima)	24 × 24 × 7/8"	☐	0.80 •	26	N/A	Class A	•	•	N/A	•	•	N/A	•
ULTIMA® Health Zone™ CREATE!™ Square Lay-in for 15/16" Prelude XL	Z1935UC1	24 × 24 × 3/4"	☐	0.70 •	38 •	BETTER	Class A	Bio-Block+	•	•	•	•	•	•
ULTIMA® Health Zone™ CREATE!™ Tegular for 9/16" Silhouette XL ONLY; 1/4" or 1/8" Reveal	Z1936UC1	24 × 24 × 3/4"	☐	0.70 •	38 •	BETTER	Class A	Bio-Block+	•	•	•	•	•	•


NOTE: Replacement panels may vary slightly in color due to material variations over time. Product could have slight color variation from run to run; adequate attic stock should be ordered. Ultima Health Zone ceilings have different scrim surface than Ultima or Optima which may affect color.

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)
Based on image/color coverage, NRC may vary slightly.
Create! panels are intended for printed visuals only. Looking for solid colors? Choose Calla® or Lyra® ceiling panels.


SUSPENSION SYSTEMS




Vector® Panel and Prelude® XL®
(White suspension required for Vector)



Tegular Panel and Silhouette® XL® 1/4" Reveal



Tegular Panel and Silhouette® XL® 1/8" Reveal



Lay-in Panel and Prelude® XL® or 360° Painted Grid

PHYSICAL DATA

Material
Ultima/Ultima Health Zone: Wet-formed mineral fiber
Optima: Fiberglass with DuraBrite® acoustically transparent membrane with CAC-backing

Surface Finish
Factory-applied latex paint with UV printing

Fire Performance
Class A: ASTM E84 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification
Ultima/Ultima Health Zone: Type A, Form A2.2, Pattern E
Optima: Type B, Form B2, Pattern E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Bacterial/Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

Ceiling tiles with BioBlock® Plus performance resist the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile (Ultima Health Zone and Optima Health Zone only). Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

Acoustical Performance
CAC testing conducted using Silhouette® suspension system.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines

Insulation Value

Ultima/Ultima Health Zone:	Optima:
R Factor – 1.6 (BTU units)	R Factor – 4.0 (BTU units)
R Factor – 0.28 (Watts units)	R Factor – 0.70 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System.
1-year limited warranty on color.
Details at armstrongceilings.com/warranty

Weight
Ultima/Ultima Health Zone: 1.05 LBS/SF
Optima: 0.55 LBS/SF

Minimum Order Quantity
2 carton (8 PCS); order by the piece
NOTE: Multiple images may require additional print setup fees.

TechLine / 1 877 276-7876
armstrongceilings.com/create

BPCS-4949-126

LEED® is a trademark of the U.S. Green Building Council; UL is a registered trademark of UL LLC; Adobe® and Illustrator® are registered trademarks of Adobe Systems Incorporated; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2026 AWI Licensing LLC

Armstrong® World Industries