KITCHEN ZONE™

Square Lay-in
smooth texture

SUSTAIN®
High Performance
Sustainable
Ceiling Systems

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Kitchen Zone 24" × 24" panels with Prelude XL 15/16" suspension system

Panels meet USDA/FSIS guidelines. A better option than vinyl-covered gypsum; panels offers a lower cost, lighter weight option, with more pieces per carton.

KEY SELECTION ATTRIBUTES

- new Kitchen Zone™ panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- Easier to cut with less dust
- Recyclable through Armstrong Recycling Program
- Brighter visual with 20% more light reflectance than vinyl-covered gypsum
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Durable – Water-repellent, Washable, Scratch-resistant, Soil-resistant
- Smooth surface meets USDA/FSIS guidelines for use in food processing areas
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

TYPICAL APPLICATIONS

- Kitchen/food preparation areas
- Laboratories
- Cafeterias
- Lavatories/restrooms

COLOR

White
(WH)

DETAILS





1. Kitchen Zone™ Lay-in
2. Kitchen Zone™ Lay-in with Prelude® 15/16" suspension system

TechLine 877 276-7876
armstrongceilings.com/kitchenzone

Armstrong®
World Industries

KITCHEN ZONE™

Square Lay-in
smooth texture

SUSTAIN®
High Performance
Sustainable Ceiling Systems

Declare.

RECYCLED CONTENT
UP TO
36%

LEED V5
Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

PERFORMANCE SELECTION

Dots represent high level of performance.

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	NRC	+	CAC	=	Total Acoustics[1]	Fire Performance	Light Reflect	Bio-Block Anti-Mold/ Mildew	Humi-Guard+ Sag Resistant	Humi-Guard+ Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels Fog/ Spray	CleanAssure™ Disinfectable Panels Wipe	DURABILITY Water Repel	DURABILITY Wash	DURABILITY Scratch	DURABILITY Soil	Recycle Program	30-Yr Warranty
KITCHEN ZONE™ 15/16" Square Lay-in	1	**673**	24 × 24 × 5/8"	N/A		33		N/A	Class A	0.89	•	•	•	•	•	•	•	•	•	•	•
		672	24 × 48 × 5/8"	N/A		33		N/A	Class A	0.89	•	•	•	•	•	•	•	•	•	•	•

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEM

15/16"



Prelude®

PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less.

ASTM E1264 Classification
Type A, Form A3.2, Pattern G; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Insulation Value
R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

Application Consideration
Not designed for use in close proximity to commercial grease ducts.

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
672 – 0.82 LBS/SF; 96 SF/CTN
673 – 0.82 LBS/SF; 64 SF/CTN

Minimum Order Quantity
1 carton

MINERAL FIBER – Standard

TechLine / 1 877 276-7876
armstrongceilings.com/kitchenzone

BPCS-4667-726

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2026 AWI Licensing LLC

Armstrong® World Industries