# CASTWORKS™ Metaphors®

## Coffers and Infill Panels

architectural forms

SUSTAIN™
High Performance
Sustainable
Ceiling Systems

FAST 4 WEEKS or Less

FAST134
Select Items Ship Fast
armstrongceilings.com/fast134



CastWorks Metaphors Cove Coffers with Ultima® Lay-in infill panels

**Coffers available in 5 designs and 4 standard colors with a range of acoustical or design infill panels. Enhanced acoustics performance options available.**

### KEY SELECTION ATTRIBUTES

- Five different coffer designs in four standard colors
- Infill panels available in Infusions®, MetalWorks™, WoodWorks®, and Ultima® panels
- CastWorks™ Metaphors® coffers are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Enhance acoustics with MetalWorks perforated or Ultima infill panels (NRC 0.70-0.90)
- Made-to-order Calla® and Lyra® infill panels available in any color
- Custom options:
  - Coffers available in coordinating custom colors
  - Suspension systems available in coordinating custom colors
- Select products included in the FAST134 program – ready to ship in 4 weeks or less
- Build America, Buy America (BABA) Act compliant

### COLORS – COFFERS

White (WH)

Silver Grey (SG)

Gun Metal Grey* (MY)

Black* (BL)

Custom Colors Available!

### CASTWORKS METAPHORS COFFER STYLES



CastWorks Metaphors Crown



CastWorks Metaphors Cove



CastWorks Metaphors Convex



CastWorks Metaphors Bead



CastWorks Metaphors Linear

Coffers with Ultima infill panel, Suprafine® XL® 9/16" suspension system

### METAPHORS INFILL PANEL SELECTION

#### Infusions

Clear Arbor (TCA)

Blue Arbor (TBA)

Refined Kiwi (TRK)

Refined Reef (TRR)

Refined Lagoon (TRL)

Refined Plum (TRP)

Refined Tangerine (TRT)

#### MetalWorks

Whitelume (WHA)

Silverlume (SIA)

Gun Metal (MYA)

Black (BL)

#### MetalWorks Perforations

M1 (Unperforated)

M2 (Microperforated)

#### WoodWorks® Natural Variations™ (Real Wood Veneers)

Maple (NMP)

Light Cherry (NLC)

Dark Cherry (NDC)

Walnut (NWN)

Oak (NOK)

Walnut Espresso (NWE)

#### Ultima

White (WH)

NOTE: For details about premium and custom infill panel patterns, perforations, and finishes, contact TechLine at 1 877 276-7876.

* Not part of the Sustain® portfolio

Due to printing limitations, shade may vary from actual product.

Armstrong® World Industries

TechLine 877 276-7876

armstrong.com/metaphorscoffers

# CASTWORKS™ Metaphors®

## Coffers and Infill Panels

architectural forms

SUSTAIN™ High Performance Sustainable Ceiling Systems

Declare.

**LEED V5**

| COMMON MATERIALS FRAMEWORK | | Climate Health | EPD |
|---|---|---|---|
| Human Health | Declare Label | Ecosystem Health | EPD |
| | HPD | | |
| | 3rd Party CDPH | Circular Economy | |
| OCCUPANT EXPERIENCE | | Acoustics | |

## VISUAL SELECTION

## PERFORMANCE

Dots represent high level of performance.

| | Item No. ◆ | Description | Dimensions Nominal W × L × H (Inches) | | Fire Performance | Recycled Content | Recycle Program | Warranty |
|---|---|---|---|---|---|---|---|---|
| CASTWORKS™ Metaphors® Coffers<br>9/16" or 15/16"<br>For additional infill panel patterns, perforations, and finishes, contact TechLine at 1 877 276-7876. | **5726_ _** | Crown Coffer | 24 × 24 × 3" |  | Class A | Std | N/A | 1-Yr |
| | **5727_ _** | Cove Coffer | 24 × 24 × 3" |  | Class A | Std | N/A | 1-Yr |
| | **5725_ _** | Convex Coffer | 24 × 24 × 1.94" |  | Class A | Std | N/A | 1-Yr |
| | **5728_ _** | Bead Coffer | 24 × 24 × 1.25" |  | Class A | Std | N/A | 1-Yr |
| | **5729_ _** | Linear Coffer | 24 × 24 × 2" |  | Class A | Std | N/A | 1-Yr |


**FAST134 program items ready to ship from manufacturer in 4 weeks or less.**
**Up-to-date lead times and product options (sizes and colors) at armstrongceilings.com/fast134**


| | | | | | |
|---|---|---|---|---|---|
| CASTWORKS Metaphors Coffers Infill Panels<br>Square Lay-in | **6541_ _ _** | Infusions® Infill Panel | Class A | Std | N/A | 1-Yr |
| Square Tegular | **6448M1_ _ _** | MetalWorks Infill Panel Unperforated (M1) | Class A | Std | N/A | 1-Yr |
| | **6448M2_ _ _** | MetalWorks Infill Panel Microperforated (M2) | | | | |
| Square Tegular | **6447W1_ _ _** | WoodWorks® Infill Panel | Class A | • | N/A | 1-Yr |
| Beveled Tegular | **1918A** | Ultima® Infill Panel* | Class A | • | • | • |


◆ Add 2- or 3-letter color suffix item number when specifying or ordering (e.g., 6541 T R K). For perforated items, include the 2-digit perforation suffix and 3-letter color suffix (e.g., 6448M1 S G and 6447W1 N M P).
* Made-to-order Calla® and Lyra® infill panels also available. Contact ABPSpecials@armstrongceilings.com to request a quote.


## SUSPENSION SYSTEMS


15/16"* or 9/16"


Suprafine® suspension system with Crown Coffer


Suprafine suspension system with Cove Coffer


Suprafine suspension system with Convex Coffer


Suprafine suspension system with Bead Coffer


Suprafine suspension system with Linear Coffer

* 15/16" not shown

## PHYSICAL DATA

**Material**
5725, 5726, 5727, 5728, 5729 – Glass fiber reinforced gypsum coffer; 6541 – Polycarbonate; 6448 – Aluminum .040" thickness; 6447 – Fire retardant particle board with face-cut veneers, California Air Resources Board (CARB) Compliant; 1918 – Wet-formed mineral fiber

**Surface Finish**
6541 – Smooth; 6448 – Factory-applied powder-coated finish (post-coated); Bare Steel, unfinished; Lacquered Steel, factory-applied lacquered finish; 6447 – Clear or tinted semi-gloss coating; 1918 – DuraBrite® with factory-applied latex paint

**Fire Performance**
All items except 6541 – Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less. 6541 – Infusions panels have been tested according to the NFPA 286 and are equivalent to Class A Interior Finish as defined by the International Building Code. Designers and installers are advised to consult a fire protection engineer, NFPA 13, and local codes for guidance where automatic fire detection and suppression systems are present.

**ASTM E1264 Classification**
6448 – Fire Class A; Unperforated – Type XX, Pattern G; Perforated – Type X, Pattern C; 6447 – Composite – Fire Class A; 1918 – Type IV, Form 2, Pattern E, Fire Class A

**Insulation Value**
1918 – R Factor 2.2 (BTU units)
R Factor 0.39 (Watts units)

**VOC Emissions**
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL™ Building Challenge, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Application Considerations**
Clear plenum height must be at least 9" to accommodate 24" x 24" CastWorks Metaphors Coffers. Bead profile requires only 5". Coffers are intended for full panel installation only. Do not cut.

**FAST134 Program Considerations**
Size of Job Matters: Big jobs, over 2500 SF or 50 pieces for shapes/vertical elements will have longer lead times.

Location Matters: Transit time not included. We are ready to ship in 1 week on FAST1 items. However, transit to the states west of Wyoming may add time.

Distributor Truck Schedule Matters: We rely on distribution to help move products around the country. When speed matters, work with your local distributor to ensure FAST134 service.

Stock vs Made-to-Order Matters: FAST3 & FAST4 items are made-to-order and will ship direct to distributor. FAST1 (stocked items) will go through distribution and depend on distributor truck schedules.

**Seismic Restraint**
Engineered, tested, and approved for application in all seismic areas.

**Warranty**
One (1) year limited warranty. Details at armstrong.com/warranty

**Weight; Square Feet/Carton**
5725 - 1.98 lbs./sq. ft.; 20 sq. ft./ctn.; 5 pcs./ctn.
5726 - 1.88 lbs./sq. ft.; 20 sq. ft./ctn.; 5 pcs./ctn.
5727 - 1.95 lbs./sq. ft.; 20 sq. ft./ctn.; 5 pcs./ctn.
5728 - 1.63 lbs./sq. ft.; 20 sq. ft./ctn.; 5 pcs./ctn.
5729 - 1.45 lbs./sq. ft.; 20 sq. ft./ctn.; 5 pcs./ctn.
6541 – 0.8 lbs./sq. ft.; 13.5 sq. ft./ctn.; 6 pcs./ctn.
6448 – 0.89 lbs./sq. ft.; 22.5 sq. ft./ctn.
6447 – 2.75 lbs./sq. ft.; 22.5 sq. ft./ctn.; 10 pcs./ctn.
1918 – 1.08 lbs./sq. ft.; 22.5 sq. ft./ctn.; 10 pcs./ctn.

**Minimum Order Quantity**
4 cartons

TechLine / 1 877 276-7876
armstrongceilings.com/metaphorscoffers

BPCS-3617-1026

LEED® is a registered trademark of the U.S. Green Building Council; Living Building Challenge® (LBC) is a registered trademark of the International Living Future Institute®; WELL™ and WELL Building Standard™ are trademarks of the International WELL Building Institute; UL and UL Certified are trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2026 AWI Licensing LLC

Armstrong® World Industries

ARCHITECTURAL FORMS – Standard