# ULTIMA®
# ULTIMA® High NRC

Square Lay-in
fine texture

TOTAL ACOUSTICS®
Sound Absorption (NRC)
+ Sound Blocking (CAC)

SUSTAIN®
High Performance
Sustainable
Ceiling Systems

CAD/Revit® drawings at:
armstrong.com/cadrevit



new *A ceiling that saves energy! Learn more*



Ultima Square Lay-in panels with Prelude XL 15/16" suspension system

**Smooth-texture panels that are washable, impact- and scratch-resistant with a non-directional visual; offers both Sustain® and Total Acoustics® panel performance for flexible spaces.**

## KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Ultima® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface

new
- High sound absorption options available up to 0.85 NRC
- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- Ceiling-2-Ceiling™ Post-consumer Recycled Content options: Items 1910HRC, 1913HRC 71% Pre-consumer; 15% Post-consumer
- USDA-Certified Biobased Product – 95%
- Items available with AirGuard® coating which actively removes formaldehyde from indoor air
- Item 1910 available with Create!™ printed images and patterns

- Non-directional visual reduces scrap and installation time
- Compatible with the TechZone® Ceiling Systems
- 30-Year Limited System Warranty against visible sag
- 10-Year replacement panel available for items 1910, 1913

10-YEAR REPLACEMENT PANEL AVAILABILITY

- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant


## TYPICAL APPLICATIONS

- Offices – closed spaces for privacy and confidentiality; open spaces for focus, collaboration, and teaming
- Healthcare – assists in addressing HIPAA, HCAHPS, and FGI acoustical requirements
- Classrooms
- Corridors
- Lobbies/reception areas
- Department stores/retail

## COLOR

White
(WH)

## DETAILS







1. Ultima® Square Lay-in
2. Ultima® Square Lay-in with Prelude® XL® 15/16" suspension system

new 

*Ultima Templok Energy Saving Ceilings*

TechLine 877 276-7876
armstrong.com/ultima

Armstrong®
World Industries

# ULTIMA®
# ULTIMA® High NRC

## Square Lay-in
## fine texture

USDA CERTIFIED BIOBASED PRODUCT PRODUCT 95%

CLOSED LOOP RECYCLED CONTENT CEILING-2-CEILING

SUSTAIN® High Performance Sustainable Ceiling Systems

Declare.

**RECYCLED CONTENT** UP TO **87%**

**LEED V5** Ecomedes Data

COMMON MATERIALS FRAMEWORK

| | | | |
|---|---|---|---|
| Human Health | Declare Label | Climate Health | EPD |
| | HPD | Ecosystem Health | EPD |
| | 3rd Party CDPH | Circular Economy | ✓ |
| OCCUPANT EXPERIENCE | | Acoustics | ✓ |

## VISUAL SELECTION

## PERFORMANCE SELECTION

Dots represent high level of performance. $$$$

| armstrongceilings.com/suspdwgs | Susp. Dwg. | | Item No. | Dimensions (Inches) | UL Classified Acoustics NRC | UL Classified Acoustics CAC | Total Acoustics[1] NRC + CAC | Fire Performance | Light Reflect | Bio-Block Anti-Mold/Mildew | Humi-Guard+ Sag Resistant | Certified Low VOC Emissions | CleanAssure™ Disinfectable Panels Fog | DURABILITY Wash | DURABILITY Impact | DURABILITY Scratch | DURABILITY Soil | Recycle Program | 30-Yr Warranty |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **ULTIMA® High NRC** | 1 | new | **2080** | 24 × 24 × 1" | 0.85 • | 35 • | BEST | Class A | 0.85 • | • | • | • | • | • | • | • | • | • | • |
| 15/16" Square Lay-in | | new | **2083** | 24 × 48 × 1" | 0.85 • | 35 • | BEST | Class A | 0.85 • | • | • | • | • | • | • | • | • | • | • |
| | | | **1940** | 24 × 24 × 7/8" | 0.80 • | 35 • | BEST | Class A | 0.87 • | • | • | • | • | • | • | • | • | • | • |
| | | | **1943** | 24 × 48 × 7/8" | 0.80 • | 35 • | BEST | Class A | 0.87 • | • | • | • | • | • | • | • | • | • | • |
| | | | **1432** | 24 × 60 × 7/8" | 0.80 • | 35 • | BEST | Class A | 0.87 • | • | • | • | • | • | • | • | • | • | • |
| | | | **1435** | 24 × 72 × 7/8" | 0.80 • | 35 • | BEST | Class A | 0.87 • | • | • | • | • | • | • | • | • | • | • |
| | | | | 7/8" & 1" Thick – 15/16" Square Lay-in | | | | | | | | | | | | | | | |
| **Made-to-Order Sizes** | | | Width (short side) | Length (long side) | N/A | N/A | N/A | Class A | 0.87 • | • | • | • | • | • | • | • | • | • | • |
| 1 Ctn Min FASTSIZE 3 WEEKS order to ship | | | 4" – 30" | 12" – 72" | | | | | | | | | | | | | | | |


Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrong.com

MORE ITEMS ▶

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
**GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

## SUSPENSION SYSTEMS

15/16"



Prelude®

**Blizzard White – Suspension System Finish**
A color and texture coordinated suspension system to complement Ultima® ceiling panels for a monolithic look and feel.

## PHYSICAL DATA

**Material**
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane

**Surface Finish**
DuraBrite scrim with factory-applied latex paint

**Fire Performance**
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

**ASTM E1264 Classification**
Type A, Form A2.2, Pattern E;
Fire Class A

**Humidity/Sag Resistance**
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustical Performance**
CAC testing conducted using Prelude® XL® suspension system.

**Primary (Embodied) Energy**
See all LCA information on our EPDs.

**High Recycled Content**
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

**Insulation Value**
2083, 1940, 1943, 1432, 1435 – R Factor – 2.2 (BTU units)
R Factor – 0.39 (Watts units)
2080, 2081 – R Factor - 2.9 (BTU units); 0.445 (Watts units)

**Cleaning and Disinfecting**
Cleaning and CDC-recommended disinfecting options available on armstrong.com/cleaning

**30-Year Performance Guarantee & Warranty**
When installed with Armstrong® Suspension System. Details at armstrong.com/warranty

**Weight; Square Feet/Carton**
1940 – 1.14 LBS/SF; 40 SF/CTN
1943 – 1.125 LBS/SF; 48 SF/CTN
1432 – 1.05 LBS/SF; 60 SF/CTN
1435 – 1.04 LBS/SF; 72 SF/CTN
2080 – 1.0 LBS/SF; 40 SF/CTN
2083 – 1.0 LBS/SF; 48 SF/CTN

**Minimum Order Quantity**
1 carton

**Metric Items Available**
1940M, 1943M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine 877 276-7876
armstrong.com/ultima

Armstrong® World Industries

MINERAL FIBER – Standard

# ULTIMA®
# ULTIMA® High NRC

Square Lay-in
fine texture

USDA CERTIFIED BIOBASED PRODUCT
PRODUCT 95%

CLOSED LOOP RECYCLED CONTENT
CEILING-2-CEILING

SUSTAIN®
High Performance
Sustainable Ceiling Systems

Declare.

RECYCLED CONTENT
UP TO 87%

LEED V5
Ecomedes Data

COMMON MATERIALS FRAMEWORK

| | | | |
|---|---|---|---|
| Human Health | Declare Label | Climate Health | EPD |
| | HPD | Ecosystem Health | EPD |
| | 3rd Party CDPH | Circular Economy | ✓ |
| OCCUPANT EXPERIENCE | | Acoustics | ✓ |

## VISUAL SELECTION

## PERFORMANCE SELECTION

Dots represent high level of performance. $$$$

| armstrongceilings.com/suspdwgs | Susp. Dwg. | Item No. | Dimensions (Inches) | UL Classified Acoustics NRC | + CAC | = | Total Acoustics[1] | Fire Performance | Light Reflect | Bio-Block Anti-Mold/ Mildew | Humi-Guard+ Sag Resistant | Certified Low VOC Emissions | CleanAssure™ Disinfectable Panels Fog | Wash | DURABILITY Impact | Scratch | Soil | Recycle Program | 30-Yr Warranty |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **ULTIMA®** 15/16" Square Lay-in | 15 | **1420** | 6 × 48 × 3/4" | N/A | N/A | | N/A | Class A | 0.88 | • | • | • | • | • | • | • | • | • | • |
| | | **1425** | 6 × 60 × 3/4" | N/A | N/A | | N/A | Class A | 0.88 | • | • | • | • | • | • | • | • | • | • |
| | | **1990** | 12 × 48 × 3/4" | 0.65* | N/A | | N/A | Class A | 0.88 | • | • | • | • | • | • | • | • | • | • |
| HRC items not included in made-to-order panels. | | **1991** | 12 × 60 × 3/4" | 0.65* | N/A | | N/A | Class A | 0.88 | • | • | • | • | • | • | • | • | • | • |
| | | **1992** | 12 × 72 × 3/4" | 0.65* | N/A | | N/A | Class A | 0.88 | • | • | • | • | • | • | • | • | • | • |
| | | **1910** **1910HRC**** | 24 × 24 × 3/4" 24 × 24 × 3/4" | 0.75 • | 35 • | | BETTER | Class A | 0.88 • | • | • | • | • | • | • | • | • | • | • |
| | | **1913** **1913HRC**** | 24 × 48 × 3/4" 24 × 48 × 3/4" | 0.75 • | 35 • | | BETTER | Class A | 0.88 • | • | • | • | • | • | • | • | • | • | • |
| | new | **4333** | 30 × 30 × 3/4" | 0.75 • | 35 • | | BETTER | Class A | 0.88 • | • | • | • | • | • | • | • | • | • | • |
| | | **1984** | 24 × 60 × 3/4" | 0.75 • | 35 • | | BETTER | Class A | 0.88 • | • | • | • | • | • | • | • | • | • | • |
| | new | **4335** | 30 × 60 × 3/4" | 0.75 • | 35 • | | BETTER | Class A | 0.88 • | • | • | • | • | • | • | • | • | • | • |
| | | **1980** | 24 × 72 × 3/4" | 0.75 • | 35 • | | BETTER | Class A | 0.88 • | • | • | • | • | • | • | • | • | • | • |
| | | | 3/4" Thick – 15/16" Square Lay-in | | | | | | | | | | | | | | | | |
| Made-to-Order Sizes | | | Width (short side) / Length (long side) | N/A | N/A | | N/A | Class A | 0.88 • | • | • | • | • | • | • | • | • | • | • |

1 Ctn Min FASTSIZE 3 WEEKS order to ship

Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrong.com

4" – 30" / 12" – 72"


[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
**GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

* Items are not UL® classified

** Ceiling-2-Ceiling™ Post-consumer Recycled Content options

## SUSPENSION SYSTEMS

15/16"



Prelude®

**Blizzard White – Suspension System Finish**
A color and texture coordinated suspension system to complement Ultima ceiling panels for a monolithic look and feel.

## PHYSICAL DATA

**Material**
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane

**Surface Finish**
DuraBrite scrim with factory-applied latex paint

**Fire Performance**
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

**ASTM E1264 Classification**
Type A, Form A2.2, Pattern E;
Fire Class A

**Humidity/Sag Resistance**
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustical Performance**
CAC testing conducted using Prelude® XL® suspension system.

**High Recycled Content**
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

**Insulation Value**
R Factor – 2.2 (BTU units); R Factor – 0.39 (Watts units)

**Cleaning and Disinfecting**
Cleaning and CDC-recommended disinfecting options available on armstrong.com/cleaning

**30-Year Performance Guarantee & Warranty**
When installed with Armstrong® Suspension System. Details at armstrong.com/warranty

**Weight; Square Feet/Carton**
1420, 1425 – 1.05 LBS/SF; 24 SF/CTN
1910, 1910HRC, 1913, 1913HRC, – 1.08 LBS/SF; 48 SF/CTN
1991 – 1.08 LBS/SF; 30 SF/CTN
1992 – 1.08 LBS/SF; 36 SF/CTN
1980 – 1.08 LBS/SF; 72 SF/CTN
1990 – 1.08 LBS/SF; 24 SF/CTN
1984 – 1.08 LBS/SF; 80 SF/CTN
4333 – 1.05 LBS/SF; 62.5 SF/CTN
4335 – 1.05 LBS/SF; 75 SF/CTN

**Minimum Order Quantity**
1 carton

**Metric Items Available**
1910M, 1913M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



TechLine 877 276-7876
armstrong.com/ultima

Armstrong® World Industries

# ULTIMA®
# ULTIMA® High NRC

## Square Lay-in
## fine texture

USDA CERTIFIED BIOBASED PRODUCT PRODUCT 95%

CLOSED LOOP RECYCLED CONTENT CEILING-2-CEILING

SUSTAIN® High Performance Sustainable Ceiling Systems

Declare.

**RECYCLED CONTENT**
UP TO **87%**

**LEED V5** Ecomedes Data

COMMON MATERIALS FRAMEWORK

| | | | |
|---|---|---|---|
| Human Health | Declare Label | Climate Health | EPD |
| | HPD | Ecosystem Health | EPD |
| | 3rd Party CDPH | Circular Economy | ✓ |
| OCCUPANT EXPERIENCE | | Acoustics | ✓ |

## VISUAL SELECTION

## PERFORMANCE SELECTION

Dots represent high level of performance. $$$$

| armstrongceilings.com/suspdwgs | Susp. Dwg. | Item No. | Dimensions (Inches) | UL Classified Acoustics NRC | + | CAC | = | Total Acoustics[1] | Fire Performance | Light Reflect | Bio-Block Anti-Mold/ Mildew | Humi-Guard+ Sag Resistant | Certified Low VOC Emissions | CleanAssure™ Disinfectable Panels Fog | Wash | DURABILITY Impact | Scratch | Soil | Recycle Program | 30-Yr Warranty |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **ULTIMA® with AirGuard™ Coating**<br>15/16" Square Lay-in<br>AirGuard™ Coating actively removes formaldehyde from indoor air. | 1 | **1900*** | 24 × 24 × 3/4" | 0.75 | | 35 | | BETTER | Class A | 0.88 | • | • | • | • | • | • | • | • | • | • |
| | | **1903*** | 24 × 48 × 3/4" | 0.75 | | 35 | | BETTER | Class A | 0.88 | • | • | • | • | • | • | • | • | • | • |

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
**GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

* Declare label does not apply to these items.

## SUSPENSION SYSTEMS

15/16"



Prelude®

**Blizzard White – Suspension System Finish**
A color and texture coordinated suspension system to complement Ultima® ceiling panels for a monolithic look and feel.

## PHYSICAL DATA

**Material**
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane

**Surface Finish**
DuraBrite scrim with factory-applied latex paint

**Fire Performance**
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

**ASTM E1264 Classification**
Type A, Form A2.2, Pattern E;
Fire Class A

**Humidity/Sag Resistance**
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustical Performance**
CAC testing conducted using Prelude® XL® suspension system.

**High Recycled Content**
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

**Insulation Value**
R Factor – 2.2 (BTU units); R Factor – 0.39 (Watts units)

**Cleaning and Disinfecting**
Cleaning and CDC-recommended disinfecting options available on armstrong.com/cleaning

**30-Year Performance Guarantee & Warranty**
When installed with Armstrong® Suspension System. Details at armstrong.com/warranty

**Weight; Square Feet/Carton**
1900, 1903, – 1.08 LBS/SF; 48 SF/CTN

**Minimum Order Quantity**
1 carton

TechLine / 1 877 276-7876
armstrong.com/ultima

BPCS-4595-1026

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2026 AWI Licensing LLC

Armstrong® World Industries

MINERAL FIBER – Standard