FELTWORKS®


Acoustical Wall Panels
medium texture

SUSTAIN®
High Performance
Sustainable
Ceiling Systems

FAST 4 WEEKS or Less
FAST134
Select Items Ship Fast
armstrong.com/fast134



CAD/Revit® drawings at:
armstrong.com/cadrevit



plus capabilities to do more



FeltWorks® Acoustical Wall Panels in Beige, Light Grey, and Dark Grey

armstrong.com/capabilities
See more photos at:
armstrong.com/photogallery

Soft visual and excellent noise control with versatile wall installation options for design flexibility.

KEY SELECTION ATTRIBUTES

- Available in three standard, nominal sizes: 24" × 48", 48" × 48", and 48" × 96"
- Quick and easy retrofit acoustical solution
- Excellent sound absorption – NRC up to 0.80
- Sustainable Beyond Standard: Custom sizes and all standard panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Select products included in the FAST134 program – ready to ship in 4 weeks or less
- Mold- and mildew-resistant surface
- No need to field-finish cut edges with color throughout panels
- Custom sizes available from 18" × 18" up to 54" × 120"
- No visible fasteners with adhesive or Z-clip installation options
- FeltWorks acoustical panels are lightweight and easy to install in most wall applications. Many install options:
  - Attachment with Z-clip and Z-bar
  - Attachment with adhesive to drywall or cement
  - Visible attachment with screw to metal furring
  - Visible attachment with direct screw

TYPICAL APPLICATIONS

- Office
- Hospitality
- Entertainment
- Retail
- Education


COLORS

Due to printing limitations, shade may vary from actual product.



White (FWH) | Beige (FBG) | Light Grey (FLG) | Dark Grey (FDG) | Black (FBL)

NOTE: Shade variance in finished products of certain colors may occur, as shown below.



Beige (FBG) | Light Grey (FLG) | Dark Grey (FDG)

DETAILS



1. Square Panel Edges (48 × 96 × 1" ONLY)
2. Beveled Panel Edges (24 × 48 × 1" and 48 × 48 × 1" ONLY)
3. Attachment with screws directly to wall (front of panel)

TechLine 877 276-7876
armstrong.com/feltworks

Armstrong® World Industries

FELTWORKS®

Acoustical Wall Panels
medium texture

SUSTAIN®
High Performance
Sustainable Ceiling Systems

Declare.

LEED V5

COMMON MATERIALS FRAMEWORK			
Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

PERFORMANCE

Dots represent high level of performance.

	Item No. ◆	Dimensions Nominal W × L × H (Inches)	Pcs/ pallet	Fire Rating	Light Reflect (White only)	Anti-Mold/ Mildew Bio-Block	Sag Resist Humi-Guard+	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels: Spray	DURABILITY: Impact	DURABILITY: Scratch
FELTWORKS® 1" Square (all sides)	**8246FWH**	48 × 96 × 1"	36	Class A	0.78	•	•	•	•	•	•
	8246FBG	48 × 96 × 1"	36								
	8246FLG	48 × 96 × 1"	36								
	8246FDG	48 × 96 × 1"	36								
	8246FBL	48 × 96 × 1"	36								
Long Edges Beveled/Short Edges Beveled*	**6322W24L048B4_ _ _**	24 × 48 × 1"	6 pcs/ ctn	Class A	0.78	•	•	•	•	•	•
	6322W48L048B4_ _ _	48 × 48 × 1"	6 pcs/ ctn	Class A	0.78	•	•	•	•	•	•
	Custom Panel Options (Square Edges Only)	W: 18" – 54" L: 18" – 120"		Class A	0.78	•	•	•	•	•	•

FAST 4 WEEKS or Less

FAST134 program items ready to ship from manufacturer in 4 weeks or less.
Up-to-date lead times and product options (sizes and colors) at armstrong.com/fast134

◆ When specifying or ordering, include the appropriate 3-digit color suffix (e.g. 8246 F W H)
NOTE: Custom panels are available by contacting ASQuote@armstrong.com
* Four-sided beveled edge panels are recommended in adjoining panel installations.

ACOUSTICAL INFORMATION

Panel Thickness	NRC	Mounting Method (Description)
1"	0.75 •	A (Adhesive)
	0.75 •	A (Screw to wall)
	0.75 •	A (Z clip to Z bar)
	0.80 •	D-20 (Screw to 7/8" metal furring)

ACCESSORIES

	Item No. ◆	Description	Color	Qty
Screw and Washer Installation	**6488_ _**	Washers	Mill Finish (paintable), Black	1000
	6489_ _	#8 × 1-7/8" Screws for washer installation	Mill Finish (paintable), Black	1000
Z-Clip and Z-Bar	**7142L04**	Light Duty Z-Clip	Off White	24
	7142L71	Light Duty Z-Bar	Off White	4
	8146PKG300	#8 × 3/4" Drill Point Screw for Z-clip installation	Zinc Plated	300

◆ When specifying or ordering, include the appropriate 2-digit color suffix MF = Mill Finish, BL = Black

ADHESIVE (BY OTHERS)

For Adhesive Installation to Painted Drywall Ceilings

Henry® 237 AcoustiGum™ or Titebond® GREENchoice™ Acoustical Ceiling Tile Adhesive

NOTE: Armstrong does not guarantee the performance of these or other adhesive products, either alone or in conjunction with Armstrong products.

PHYSICAL DATA

Material
Non-woven layered and formed polyester felt (PET) fiber panels with color throughout.

Fire Performance
Each color has its own test report per ASTM E84. Flame Spread Index 25 or less. Smoke Developed Index 450 or less. Class A.

1" FeltWorks® panel tested according to CAN/ULC S102.2-10. Flame Spread value 80. Smoke Developed Classification I/c p 425.

Acoustical Performance
FeltWorks 1" acoustical panels provide a wide range of sound absorption, from NRC 0.75 to 0.90, based on installation method used, tested per ASTM C423 and mounted in accordance with ASTM E795.

Application Considerations
Color and texture may vary from panel to panel and from order to order. Adequate attic stock should be ordered. FeltWorks panels are not approved for exterior application. FeltWorks panels should not be installed near sources of heat greater than 158 degrees F. Adjoining panel installations are not warranted.

TechLine 877 276-7876

armstrong.com/feltworks

2" spacing between panels is required on 48" × 96" panels only. 24" × 48" and 48" × 48" beveled edge panels may be installed side-by-side with no spacing.

FAST134 Program Considerations
Size of Job Matters: Big jobs, over 2500 SF or 50 pieces for shapes/vertical elements will have longer lead times.

Location Matters: Transit time not included. We are ready to ship in 1 week on FAST1 items. However, transit to the states west of Wyoming may add time.

Distributor Truck Schedule Matters: We rely on distribution to help move products around the country. When speed matters, work with your local distributor to ensure FAST134 service.

Stock vs Made-to-order Matters: FAST3 & FAST4 items are made-to-order and will ship direct to distributor. FAST1 (stocked items) will go through distribution and depend on distributor truck schedules.

Seismic Restraint
All FeltWorks panel installation options have been engineered, tested, and approved for use in all seismic areas. See installation instructions for details.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Cleaning and Disinfecting
Cleaning and CDC approved disinfecting options available on armstrong.com/cleaning

Design Support
For custom design assistance contact ProjectWorks® Design Services or visit armstrong.com/projectworks

Weight, Pieces, and SF/Pallet
8246 is shipped in pallet quantities. 6322W24L048B4 and 6322W48L048B4 panels are shipped in carton quantities.

8246 pieces per pallet will vary between 35 and 36 pieces based on color.

8246FWH: 36 pieces/pallet – 1,152 SF/pallet
8246FBG: 36 pieces/pallet – 1,152 SF/pallet
8246FLG: 36 pieces/pallet – 1,152 SF/pallet
8246FDG: 36 pieces/pallet – 1,152 SF/pallet
8246FBL: 36 pieces/pallet – 1,152 SF/pallet
6322W24L048B4: 6 pcs/carton – 48 SF/carton
6322W48L048B4: 6 pcs/carton – 96 SF/carton

Weight: 0.50 lbs/SF

Armstrong®
World Industries

FELTWORKS®

Acoustical Wall Panels
medium texture

SUSTAIN®
High Performance
Sustainable Ceiling Systems


Declare.

LEED V5

COMMON MATERIALS FRAMEWORK		Climate Health	EPD
Human Health	Declare Label	Ecosystem Health	EPD
	HPD		
	3rd Party CDPH	Circular Economy	
OCCUPANT EXPERIENCE		Acoustics	✓


INSTALLATION DETAILS


MOUNTING D-20: SCREW ATTACHMENT TO METAL FURRING



Metal furring layout (3 rows per panel) with recommended 2" gap between panels for screw & washer installation

MOUNTING A: ATTACHMENT WITH DIRECT SCREW





PARTITIONS & WALLS

FELTWORKS®

Acoustical Wall Panels
medium texture

SUSTAIN®
High Performance
Sustainable Ceiling Systems

Declare.


LEED V5

COMMON MATERIALS FRAMEWORK		Climate Health	EPD
Human Health	Declare Label	Ecosystem Health	EPD
	HPD		
	3rd Party CDPH	Circular Economy	
OCCUPANT EXPERIENCE		Acoustics	✓

INSTALLATION DETAILS




MOUNTING A: Z-CLIP AND Z-BAR ATTACHMENT






MOUNTING A: ADHESIVE ATTACHMENT



Adhesive attachment



Adhesive layout

PARTITIONS & WALLS

TechLine / 877 276-7876
armstrong.com/feltworks

BPCS-6718-826

Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute®; WELL™ and WELL Building Standard™ are trademarks of the International WELL Building Institute; Gorilla Glue® is a registered trademark of Gorilla Glue Company; Henry® and AcoustiGum™ are trademarks of W.W. Henry Company; Titebond® and GREENchoice™ are trademarks of Frankline International; UL and UL Greenguard are trademarks of UL LLC; LEED® is a registered trademark of the U.S. Green Building Council; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2026 AWI Licensing LLC

Armstrong®
World Industries