Fire Resistive Ceiling Systems

Edge Profile	Item No.	Dimensions	UL Classified Acoustics NRC	+	CAC	=	Total Acoustics[1] NRC CAC	Fire Rating	Light Reflect	Anti-Mold/ Mildew Bio-Block®	Sag Resist	Certified Low VOC Emissions	Recycle Program
CEILING PANELS													
Ceramaguard® 15/16" Square Lay-In	605	24 × 48 × 5/8"	N/A		40 •		N/A	Fire Guard™	0.86 •	•	HumiGuard® Max	•	
Ceramaguard® Fine Fissured™ 15/16" Square Lay-In	607	24 × 24 × 5/8"	0.55		38 •		N/A	Fire Guard	0.79	•	HumiGuard Max	•	
	608	24 × 48 × 5/8"	0.55		40 •		N/A	Fire Guard	0.79	•	HumiGuard Max	•	
Cirrus® 9/16" Beveled Tegular	577	24 × 24 × 3/4"	0.35		35 •		N/A	Fire Guard	0.85 •	•	HumiGuard® Plus	•	•
Cirrus 15/16" Angled Tegular	578	24 × 24 × 3/4"	0.35		35 •		N/A	Fire Guard	0.85 •	•	HumiGuard Plus	•	•
Clean Room™ VL (Unperforated) 15/16" or 1-1/2" Square Lay-In	868	24 × 24 × 5/8"	N/A		40 •		N/A	Fire Guard	0.80	•	HumiGuard Plus	N/A	N/A
	870	24 × 48 × 5/8"	N/A		40 •		N/A	Fire Guard	0.80	•	HumiGuard Plus	N/A	N/A
Cortega® 15/16" Square Lay-In	824	24 × 24 × 5/8"	0.55		35 •		N/A	Fire Guard	0.80	N/A	Std	•	•
	823	24 × 48 × 5/8"	0.55		35 •		N/A	Fire Guard	0.80	N/A	Std	•	•
Cortega 15/16" Angled Tegular	816	24 × 24 × 5/8"	0.55		35 •		N/A	Fire Guard	0.80	N/A	Std	•	•
Cortega® Second Look® II 15/16" Angled Tegular	2758	24 × 48 × 3/4"	0.55		40 •		N/A	Fire Guard	0.81	N/A	Std	•	•
Dune™ 15/16" Square Lay-In	1850	24 × 24 × 5/8"	0.50		35 •		N/A	Fire Guard	0.81	•	HumiGuard Plus	•	•
	1851	24 × 48 × 5/8"	0.50		35 •		N/A	Fire Guard	0.81	•	HumiGuard Plus	•	•
Dune 15/16" Angled Tegular	1853	24 × 24 × 5/8"	0.50		35 •		N/A	Fire Guard	0.81	•	HumiGuard Plus	•	•
Dune 9/16" Beveled Tegular	1852	24 × 24 × 5/8"	0.50		35 •		N/A	Fire Guard	0.81	•	HumiGuard Plus	•	•
Fine Fissured™ 15/16" Square Lay-In	1831	24 × 24 × 5/8"	0.55		35 •		N/A	Fire Guard	0.82	•	HumiGuard Plus	•	•
	1830	24 × 48 × 5/8"	0.55		35 •		N/A	Fire Guard	0.82	•	HumiGuard Plus	•	•
Fine Fissured 15/16" Angled Tegular	1833	24 × 24 × 5/8"	0.55		35 •		N/A	Fire Guard	0.82	•	HumiGuard Plus	•	•
	1834	24 × 24 × 5/8"	0.55		35 •		N/A	Fire Guard	0.82	•	HumiGuard Plus	•	•
Fine Fissured 9/16" Beveled Tegular	1835	24 × 24 × 5/8"	0.55		35 •		N/A	Fire Guard	0.82	•	HumiGuard Plus	•	•
Fissured 15/16" Square Lay-In	896	24 × 24 × 5/8"	0.55		35 •		N/A	Fire Guard	0.79	N/A	Std	•	•
	895	24 × 48 × 5/8"	0.55		35 •		N/A	Fire Guard	0.79	N/A	Std	•	•
Fissured 15/16" Angled Tegular	815	24 × 24 × 5/8"	0.55		35 •		N/A	Fire Guard	0.79	N/A	Std	•	•

Dots represent high level of performance.

Fire Resistive Ceiling Systems

Edge Profile	Item No.	Dimensions	UL Classified Acoustics NRC	+	CAC	=	Total Acoustics[1] NRC + CAC	Fire Rating	Light Reflect	Anti-Mold/ Mildew Bio-Block®	Sag Resist	Certified Low VOC Emissions	Recycle Program
CEILING PANELS (CONT.)													
Fine Fissured™ Second Look® 15/16" Angled Tegular	**1861**	24 × 48 × 3/4"	0.55		35 •		N/A	Fire Guard™	0.82	•	HumiGuard® Plus	•	•
School Zone® Fine Fissured™ 15/16" Square Lay-In	**1810**	24 × 24 × 3/4"	0.70 •		40 •		BETTER	Fire Guard	0.82	•	HumiGuard Plus	•	•
	1811	24 × 48 × 3/4"	0.70 •		40 •		BETTER	Fire Guard	0.82	•	HumiGuard Plus	•	•
School Zone Fine Fissured 15/16" Angled Tegular	**1820**	24 × 24 × 3/4"	0.70 •		35 •		BETTER	Fire Guard	0.82	•	HumiGuard Plus	•	•
	1824	24 × 48 × 3/4"	0.70 •		35 •		BETTER	Fire Guard	0.82	•	HumiGuard Plus	•	•
School Zone Fine Fissured 9/16" Beveled Tegular	**1821**	24 × 24 × 3/4"	0.70 •		35 •		BETTER	Fire Guard	0.82	•	HumiGuard Plus	•	•
Ultima® 15/16" Beveled Tegular	**1894**	24 × 24 × 3/4"	0.60		40 •		GOOD	Fire Guard	0.88 •	•	HumiGuard Plus	•	•
Ultima 9/16" Beveled Tegular	**1895**	24 × 24 × 3/4"	0.60		40 •		GOOD	Fire Guard	0.88 •	•	HumiGuard Plus	•	•
VL (Perforated) 15/16" or 1-1/2" Square Lay-In	**869**	24 × 24 × 5/8"	0.55		35 •		N/A	Fire Guard	0.78	•	HumiGuard Plus	N/A	N/A
	871	24 × 48 × 5/8"	0.55		35 •		N/A	Fire Guard	0.78	•	HumiGuard Plus	N/A	N/A

Product Name	Item No.	Description	Rout Spacing	Dimensions (Inches)	LOAD TEST DATA L/360 4 Ft.	L/360 5 Ft.	Seismic Category	PACKAGING Pcs/ Ctn	LFt/ Ctn
SUSPENSION SYSTEMS									
Prelude® XL® FireGuard™	**8031**	12' HD Main Beam	6" O.C.	144 × 15/16 × 1-11/16"	16.73	8.73	•	20	240
	8300	12' ID Main Beam	6" O.C.	144 × 15/16 × 1-11/16"	13.5	6.35	•	20	240
	XL8341	4' Cross Tee	12" O.C	48 × 15/16 × 1-11/16"	16.89	N/A	•	60	240
	XL8340	4' Cross Tee	12" O.C.	48 × 15/16 × 1-11/16"	12.25	N/A	•	60	240
	XL8323	2' Cross Tee	N/A	24 × 15/16 × 1-3/8"	36.0 at 2'	N/A	•	60	120
	XL8320	2' Cross Tee	N/A	24 × 15/16 × 1-11/16"	61.33 at 2'	N/A	•	60	120
Prelude® Plus XL® FireGuard™	**HD8201_ _**	12' HD Main Beam	N/A	144 × 15/16 × 1-11/16"	16.73	N/A	•	20	240
	XL8240_ _	4' Cross Tee	N/A	48 × 15/16 × 1-1/2"	12.75 at 2'	N/A	•	60	240
	XL8223_ _	2' Cross Tee	N/A	24 × 15/16 × 1-1/2"	38.63 at 2'	N/A	•	60	120
Suprafine® XL® FireGuard™	**8501**	12' HD Main Beam	6" O.C.	144 × 9/16 × 1-11/16"	16.86	10.62	•	20	240
	8500	12' ID Main Beam	6" O.C.	144 × 9/16 × 1-11/16"	12.75	5.74	•	20	240
	XL8540	4' Cross Tee	12" O.C.	48 × 9/16 × 1-11/16"	10.34	N/A	•	60	240
	XL8520	2' Cross Tee	N/A	24 × 9/16 × 1-11/16"	51.83	N/A	•	60	120

Dots represent high level of performance.

All trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC