LYRA® PB Vector®

with Plant-based Binder

Wood Looks

smooth texture

SUSTAIN®
High Performance
Sustainable
Ceiling Systems

CAD/Revit® drawings at:
armstrong.com/cadrevit



Lyra PB Vector panels in Brown Sugar Walnut with 15/16" Prelude suspension system

Wood-look visual with a 1/4" reveal and downward accessibility; ideal for projects where plenum space is limited. Offers high sound absorption.

KEY SELECTION ATTRIBUTES

- 12 wood-look visuals are now part of the Lyra® PB portfolio
- 1/4" reveal between acoustical panels results in a monolithic appearance
- Lyra PB panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- Downward accessible for minimal plenum height
- Outstanding acoustical performance for open plan areas, both Articulation Class 180 and NRC 0.90
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLORS

Due to printing limitations, shade may vary from actual product.

Standard Wood-look Visuals (15/16" Vector)

Brown Sugar Walnut (WBS)	Toffee Chestnut (WTC)	Vanilla Ash (WVA)	Honey Oak (WHO)	Bourbon Cherry (WBC)	Cashew Maple (WCM)	French Roast Walnut (WRW)	Portabella Walnut (WPW)
					new	new	new

1 Ctn. Min Order Qty in Standard Sizes, 500 SF Min Order Qty in Made-to-Order Sizes

NOTE: All wood-look panels are produced with wood grain parallel to the panel length.

Made-to-order Wood-look Visuals (15/16" Vector)

Earl Grey Teak (WGT)	Dark Mocha Walnut (WMW)	Toasted Almond Ash (WTA)	Truffle Walnut (WTW)
		new	new

500 SF Min Order Qty.; All quotes must be sent to ABPspecials@armstrong.com

DETAILS



1. Lyra® PB Vector® with Prelude® XL® 15/16" suspension system

TechLine 877 276-7876
armstrong.com/lyravector

Armstrong®
World Industries

LYRA® PB Vector®

with Plant-based Binder

Wood Looks

smooth texture

PLANT BASED BINDER

SUSTAIN® High Performance Sustainable Ceiling Systems

Declare.

RECYCLED CONTENT

UP TO 71%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

REALISTIC WOOD LOOKS, SUPERIOR ACOUSTICAL CONTROL

$$$$



Lyra PB 15/16" Vector panels in Toffee Chestnut with 15/16" Prelude suspension system in Oat

Lyra® PB wood-look panels provide the natural beauty of large format wood ceilings with superior sound absorption and sustainability attributes without the expense.

Wood-look panels:

- Feature a 1/4" reveal between lightweight, sag-resistant acoustical panels to achieve the look of large-format monolithic wood
- Have superior sound absorption (NRC 0.90) without perforations
- Are fast and easy to install on standard suspension systems

STANDARD WOOD-LOOK VISUALS (15/16" Vector)

Color-coordinated painted Vector panel edges and recommended standard Prelude® XL® Suspension System colors shown below.



Brown Sugar Walnut (WBS)



Prelude XL Suspension System in Black (BL)



Toffee Chestnut (WTC)



Prelude XL Suspension System in Oat (SOT)



Vanilla Ash (WVA)



Prelude XL Suspension System in Hay (SHY)



Honey Oak (WHO)



Prelude XL Suspension System in Hay (SHY)



Bourbon Cherry (WBC)



Prelude XL Suspension System in Black (BL)



Cashew Maple (WCM)



Prelude XL Suspension System in Oat (SOT)



French Roast Walnut (WRW)



Prelude XL Suspension System in Black (BL)



Portabella Walnut (WPW)



Prelude XL Suspension System in Black (BL)

MADE-TO-ORDER WOOD-LOOK VISUALS (15/16" Vector)

500 SF minimum order quantity. Color-coordinated painted Vector panel edges and recommended standard Prelude XL Suspension System colors shown below.



Earl Grey Teak (WGT)



Prelude XL Suspension System in Grey Stone (GS)



Dark Mocha Walnut (WMW)



Prelude XL Suspension System in Black (BL)



Toasted Almond Ash (WTA)



Prelude XL Suspension System in Medium Taupe (MT)



Truffle Walnut (WTW)



Prelude XL Suspension System in Black (BL)

NOTE: All wood-look panels are produced with wood grain parallel to the panel length.

FIBERGLASS – Standard

TechLine 877 276-7876

armstrong.com/lyravector

Armstrong® World Industries

LYRA® PB Vector®

with Plant-based Binder

Wood Looks

smooth texture

PLANT BASED BINDER

SUSTAIN® High Performance Sustainable Ceiling Systems

Declare.

RECYCLED CONTENT

UP TO 71%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

PERFORMANCE SELECTION

Dots represent high level of performance. $$$$

armstrong.com/ suspdwgs	Susp. Dwg.	Item No.		Dimensions (Inches)		UL Classified Acoustics NRC + CAC =	Total Acoustics[1]	Articulation Class AC	Fire Performance	Light Reflect	Bio-Block Anti-Mold/ Mildew	Humi-Guard+ Sag Resistant	CleanAssure™ Disinfectable Panels Fog	DURABILITY Impact	30-Yr Warranty
LYRA® with Plant-based Binder Wood-look Visuals 15/16" Vector® with 1/4" Reveal A B C D	73	**8494PBWBS** **8494PBWTC** **8494PBWVA** **8494PBWHO** **8494PBWBC** **8494PBWCM** **8494PBWRW** **8494PBWPW**	Walnut Brown Sugar Toffee Chestnut Vanilla Ash Honey Oak Bourbon Cherry Cashew Maple French Roast Walnut Portabella Walnut	24 × 24 × 7/8"		0.90 •	N/A	N/A	180 •	Class A	N/A	•	•	•	•	•
		8494PBWGT† Earl Grey Teak 8494PBWMW† Dark Mocha Walnut 8494PBWTA† Toasted Almond Ash 8494PBWTW† Truffle Walnut		24 × 24 × 7/8"		0.90 •	N/A	N/A	180 •	Class A	N/A	•	•	•	•	•
		8495PBWBS **8495PBWTC** **8495PBWVA** **8495PBWHO** **8495PBWBC** **8495PBWCM** **8495PBWRW** **8495PBWPW**	Walnut Brown Sugar Toffee Chestnut Vanilla Ash Honey Oak Bourbon Cherry Cashew Maple French Roast Walnut Portabella Walnut	24 × 48 × 7/8"		0.90 •	N/A	N/A	180 •	Class A	N/A	•	•	•	•	•
		8495PBWGT† Earl Grey Teak 8495PBWMW† Dark Mocha Walnut 8495PBWTA† Toasted Almond Ash 8495PBWTW† Truffle Walnut		24 × 48 × 7/8"		0.90 •	N/A	N/A	180 •	Class A	N/A	•	•	•	•	•
		8496PBWBS **8496PBWTC** **8496PBWVA** **8496PBWHO** **8496PBWBC** **8496PBWCM** **8496PBWRW** **8496PBWPW**	Walnut Brown Sugar Toffee Chestnut Vanilla Ash Honey Oak Bourbon Cherry Cashew Maple French Roast Walnut Portabella Walnut	24 × 72 × 7/8"		0.90 •	N/A	N/A	180 •	Class A	N/A	•	•	•	•	•
		8496PBWGT† Earl Grey Teak 8496PBWMW† Dark Mocha Walnut 8496PBWTA† Toasted Almond Ash 8496PBWTW† Truffle Walnut		24 × 72 × 7/8"		0.90 •	N/A	N/A	180 •	Class A	N/A	•	•	•	•	•
		8497PBWBS **8497PBWTC** **8497PBWVA** **8497PBWHO** **8497PBWBC** **8497PBWCM** **8497PBWRW** **8497PBWPW**	Walnut Brown Sugar Toffee Chestnut Vanilla Ash Honey Oak Bourbon Cherry Cashew Maple French Roast Walnut Portabella Walnut	24 × 96 × 7/8"		0.90 •	N/A	N/A	180 •	Class A	N/A	•	•	•	•	•
		8497PBWGT† Earl Grey Teak 8497PBWMW† Dark Mocha Walnut 8497PBWTA† Toasted Almond Ash 8497PBWTW† Truffle Walnut		24 × 96 × 7/8"		0.90 •	N/A	N/A	180 •	Class A	N/A	•	•	•	•	•
		8498PBWBS **8498PBWTC** **8498PBWVA** **8498PBWHO** **8498PBWBC** **8498PBWCM** **8498PBWRW** **8498PBWPW**	Walnut Brown Sugar Toffee Chestnut Vanilla Ash Honey Oak Bourbon Cherry Cashew Maple French Roast Walnut Portabella Walnut	30 × 30 × 7/8"		0.90 •	N/A	N/A	180 •	Class A	N/A	•	•	•	•	•
		8498PBWGT† Earl Grey Teak 8498PBWMW† Dark Mocha Walnut 8498PBWTA† Toasted Almond Ash 8498PBWTW† Truffle Walnut		30 × 30 × 7/8"		0.90 •	N/A	N/A	180 •	Class A	N/A	•	•	•	•	•
		7/8" Thick – 15/16" Vector													
Made-to-order Sizes and Colors for Wood-look Panels 3-4 WEEKS order to ship		Width (short side) 12" – 30" 36" – 48"		Length (long side) 12" – 96" 12" – 48"		N/A	N/A	N/A	N/A	Class A	N/A	•	•	•	•	•

Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrong.com

Wood looks are not available via the FastSize™ program.

† Made-to-order item. 500 SF minimum order quantity applies.

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

FIBERGLASS – Standard

TechLine 877 276-7876

armstrong.com/lyravector

Armstrong® World Industries

LYRA® PB Vector®

with Plant-based Binder

Wood Looks

smooth texture

PLANT BASED BINDER

SUSTAIN® High Performance Sustainable Ceiling Systems

Declare.

RECYCLED CONTENT

UP TO 71%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK


Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

ACCESSORIES (must be ordered separately)

Item No.		
441		Border Clip for Vector® panels (required for installations with the suspension system resting on the wall molding). Primarily used for corners and special cutouts.
442		Hold-down Clip for Vector® panels (for all installations)
7425 (24"), **7431** (30"), **7445** (48"), **7461** (60")		Stabilizer Bars
523		Midpoint Clip (Needed for panels over 30" wide)
7870		Spring Border Clip (For installations with the panel resting on the wall molding)

SUSPENSION SYSTEM

15/16"



Prelude® XL®

PHYSICAL DATA

Material
Fiberglass with plant-based binder and acoustically transparent membrane

Surface Finish
Acoustically transparent membrane with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification
Type B, Form B2, Pattern G; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Design Considerations
Use fixture trim kit around all lights, diffusers, and other ceiling penetrations to avoid exposed suspension system and panel edges.

Physical product samples for standard and custom colors are available upon request. Please refer to the physical product sample prior to making a final selection. While we strive to ensure exact color matches, various factors such as differences in materials, texture, substrate porosity, painting processes, lighting, and observer subjectivity can all affect how paint colors appear on ceiling and wall panels, suspension systems, and trim products. Due to these and other differences, ceiling and wall panels, trim products, and suspension systems with the same color name will coordinate but may not be an exact color match. Order sufficient initial quantities and attic stock to minimize possible color variation.

Design Consideration: Wood-Look Panels
All wood-look panels are produced with wood grain parallel to the panel length. Wood-look visuals are not dye-lotted, but are designed to mimic slight color variations as seen in real wood.

Insulation Value
R Factor – 4.4 (BTU units); R Factor – 0.70 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrong.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrong.com/warranty

Weight; Square Feet/Carton
8494PB – 0.58 LBS/SF; 48 SF/CTN
8495PB, 8497PB – 0.58 LBS/SF; 96 SF/CTN
8496PB – 0.58 LBS/SF; 72 SF/CTN
8498PB – 0.58 LBS/SF; 75 SF/CTN

Minimum Order Quantity
1 carton for all standard items in 15/16" Vector
500 SF minimum order quantities apply to wood-look visuals WGT, WMW, WTA, WTW, and made-to-order sizes in all wood-look visuals.

FIBERGLASS – Standard

TechLine / 877 276-7876
armstrong.com/lyravector

BPCS-7132-926

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2026 AWI Licensing LLC

Armstrong® World Industries