PUEBLO™
PUEBLO High NRC

Square Lay-in & Tegular
smooth texture

SUSTAIN®
High Performance
Sustainable
Ceiling Systems

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Pueblo Beveled Tegular panels with Suprafine® XL® 9/16" suspension system

Smooth texture acoustical panel with good sound absorption and sound-blocking performance for a wide variety of open-plan spaces.


KEY SELECTION ATTRIBUTES

- Good combination of sound absorption and sound blocking; up to NRC 0.90 and CAC 30
- Pueblo™ panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Mold- and mildew-resistant surface
- Smooth, white surface
- Product can be recycled through the Armstrong Ceilings Recycling Program
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant
- 30-Year Limited System Warranty against visible sag, mold, and mildew

COLOR

White
(WH)

DETAILS



1. Pueblo Square Lay-in
2. Pueblo Beveled Tegular

TechLine 877 276-7876
armstrongceilings.com/pueblo

Armstrong®
World Industries

PUEBLO™
PUEBLO High NRC

Square Lay-in & Tegular
smooth texture

SUSTAIN®
High Performance
Sustainable Ceiling Systems

Declare.

RECYCLED CONTENT
UP TO 70%

LEED V5
Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health
	HPD	Ecosystem Health
	3rd Party CDPH	Circular Economy ✓
OCCUPANT EXPERIENCE		Acoustics ✓

VISUAL SELECTION

PERFORMANCE SELECTION


Dots represent high level of performance. $$$$

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)		UL Classified Acoustics NRC	+ CAC	=	Total Acoustics[1]	Fire Performance	Light Reflect	Bio-Block Anti-Mold/ Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	Durability	Recycle Program	30-Yr Warranty
new PUEBLO™ High NRC 15/16" Square Lay-in	1	1864	24 × 24 × 1"	□	0.90 •	30		N/A	Class A	0.82	•	•	•	Std	•	•
		1865	24 × 48 × 1"	▭	0.90 •	30		N/A	Class A	0.82	•	•	•	Std	•	•
9/16" Beveled Tegular	1	1866	24 × 24 × 1"	□	0.90 •	30		N/A	Class A	0.82	•	•	•	Std	•	•
		1867	24 × 48 × 1"	▭	0.90 •	30		N/A	Class A	0.82	•	•	•	Std	•	•
15/16" Beveled Tegular	1	1868	24 × 24 × 1"	□	0.90 •	30		N/A	Class A	0.82	•	•	•	Std	•	•
		1869	24 × 48 × 1"	▭	0.90 •	30		N/A	Class A	0.82	•	•	•	Std	•	•
PUEBLO™ 15/16" Square Lay-in	1	1812	24 × 24 × 3/4"	□	0.70 •	30		N/A	Class A	0.82	•	•	•	Std	•	•
		1837	24 × 48 × 3/4"	▭	0.70 •	30		N/A	Class A	0.82	•	•	•	Std	•	•
9/16" Beveled Tegular	1	1813	24 × 24 × 3/4"	□	0.70 •	30		N/A	Class A	0.82	•	•	•	Std	•	•
		1838	24 × 48 × 3/4"	▭	0.70 •	30		N/A	Class A	0.82	•	•	•	Std	•	•
15/16" Beveled Tegular	1	1814	24 × 24 × 3/4"	□	0.70 •	30		N/A	Class A	0.82	•	•	•	Std	•	•
		1839	24 × 48 × 3/4"	▭	0.70 •	30		N/A	Class A	0.82	•	•	•	Std	•	•

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.


SUSPENSION SYSTEMS

15/16"




Prelude® XL®


9/16"




Silhouette® 1/4" Reveal



Silhouette 1/8" Reveal



Suprafine®



Interlude®

PHYSICAL DATA

Material
Wet-formed mineral fiber with acoustically transparent membrane.

Surface Finish
Acoustically transparent membrane with factory-applied latex paint.

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL® labeled).

ASTM E1264 Classification
Type A, Form A2.2, Pattern G; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling panels with BioBlock® performance resist the growth of mold and mildew on the panel surface.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude XL suspension system for 15/16" edge detail and Silhouette suspension system for 9/16" edge detail.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value
1812, 1813, 1814, 1837, 1838, 1839 –
R Factor – 2.1 (BTU units)
R Factor – 0.27 (Watts units)
1864, 1865, 1866, 1867, 1868, 1869 –
R Factor - 2.9 (BTU units)
R Factor - 0.445 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System.
Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1812, 1837 – 1.08 LBS/SF; 48 SF/CTN
1813, 1814, 1838, 1839 – 1.05 LBS/SF; 48 SF/CTN
1866, 1868 – 1.09 LBS/SF; 32 SF/CTN
1867, 1869 – 1.09 LBS/SF; 48 SF/CTN
1864 – 1.12 LBS/SF; 32 SF/CTN
1865 – 1.12 LBS/SF; 48 SF/CTN

Minimum Order Quantity
1 carton

TechLine / 1 877 276-7876
armstrongceilings.com/pueblo

BPCS-6266-925

LEED® is a registered trademark of the U.S. Green Building Council; Living Building Challenge® (LBC) is a trademark of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong® World Industries

MINERAL FIBER – Standard