HumiGuard® Ceiling Panel
Ten (10) Year Limited Warranty

EFFECTIVE NOVEMBER 2026

Please read the following terms carefully, as they are affected by the installation conditions. Armstrong World Industries does not assume nor does it authorize any person to assume or extend on its behalf any other warranty obligation or liability. This express warranty constitutes the entire obligation of Armstrong World Industries, Inc. and there are no other warranties expressed or implied, including any warranty of merchantability or fitness for any purpose whatsoever.

(Applies only to products designated as HumiGuard® Max and HumiGuard Plus in the product catalog.)

Armatuff®	Backstage Noir®	Calla®	Calla® Health Zone™	Calla® Health Zone™ AirAssure®	Calla® High CAC	Calla® High NRC
Calla® Privassure®	Calla® Templok®	Calla® Vector®	Canyon®	Capz™	Ceramaguard®	Ceramaguard® Fine Fissured™
Cirrus®	Clean Room™ FL	Create!™	DataZone™	DesignStackz™	Dune™	Dune™ Second Look®
Fine Fissured™	Fine Fissured™ Second Look®	Georgian™	Graphis® Rustex™	InvisAcoustics™ Black and White	Kitchen Zone™	Lyra®
Lyra® PB Wood Looks	Lyra® Vector®	Lyra® Concealed	Lyra® High CAC	Lyra® Direct Apply	Lyra® PB Vector® Wood Looks	Mesa™
Optima®	Optima® Plank	Optima® Vector	Optima® Concealed	Pebble™	Pueblo®	Random Fissured™
School Zone® Fine Fissured™	School Zone® Fine Fissured™ AirAssure®	Shasta®	TechZone®	Tundra®	Ultima®	Ultima® AirAssure®
Ultima® Health Zone™	Ultima® Health Zone™ AirAssure®	Ultima® High NRC	Ultima® High NRC Templok®	Ultima® Low Embodied Carbon	Ultima® Plank	Ultima® Templok®
Ultima® Vector®						

Armstrong® Commercial Ceiling products with HumiGuard Max and HumiGuard Plus performance have a ten (10) year limited warranty when installed and used under normal conditions.

Commercial Ceiling products with HumiGuard Max and HumiGuard Plus performance are warranted to be free from defects in materials or factory workmanship for ten (10) years from the date of installation, except for obvious defects in materials or factory workmanship, of which Armstrong World Industries must be notified within 30 days of the date of installation.

Commercial Ceiling panels with HumiGuard Max and HumiGuard Plus performance are warranted to be free from sagging and warping as a result of defects in materials or factory workmanship for ten (10) years from the date of installation.

Commercial Ceiling panels with BioBlock® performance are warranted to be free from the growth of mold, and mildew for ten (10) years from the date of installation. Health Zone™ commercial ceiling panels with BioBlock Plus performance are warranty to be free from the growth of mold, mildew, and odor- and stain-producing bacteria for ten (10) years from the date of installation. Ceiling panels with BioBlock performance provide broad-spectrum control for the growth of mold and mildew on the panel surface over the warranty period.

All Armstrong World Industries limited warranties are subject to use under normal conditions. Abnormal conditions include exposure to chemical fumes, vibrations, moisture from conditions such as building leaks or condensation, excessive humidity, or excessive dirt or dust buildup.

Armstrong®
World Industries

What will Armstrong World Industries do?

Subject to confirmation by Armstrong World Industries of such product failure, Armstrong will deliver, at Armstrong's expense, F.O.B., to the place of installation, new product, of the same or similar type and grade, in an amount equal to that which is determined to be defective.

What does this warranty not cover?

Damage that may occur from vibrations, fire, water, freezing temperature, accident or any form of abuse or exposure to Abnormal Conditions is not covered by this warranty. If subject to Abnormal Conditions, the products should be removed immediately and replaced once the conditions are normal.

Except for HumiGuard Max products, these products cannot be used in exterior applications. This warranty does not extend to any component of the suspension system such as, but not limited to, the metal grid or any other accessory used in the installation of the ceiling products. The ceiling product must not be used to support any other material except fiberglass thermal/sound control insulation installed in the thickness, density and manner according to Armstrong® specifications, except that Mineral Fiber ceiling products can be placed directly on top of Optima Lay In and Tegular products with prior approval by Armstrong World Industries. Except for ceilings with BioBlock Plus, HumiGuard Plus fiberglass, and HumiGuard Max mineral fiber, the growth of mold or bacteria is not covered by this warranty nor is it the responsibility of Armstrong World Industries. All products should be maintained to avoid excessive dirt or dust buildup or the presence of excessive moisture that would provide a medium for microbial growth on ceiling panels.

THIS EXPRESS WARRANTY CONSTITUTES THE ENTIRE OBLIGATION OF ARMSTRONG WORLD INDUSTRIES AND THERE ARE NO OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE WHATSOEVER. LIABILITY IS LIMITED TO THAT SET FORTH BELOW AND ARMSTRONG WORLD INDUSTRIES SHALL IN NO EVENT BE LIABLE FOR ANY INSTALLATION OR REMOVAL COST OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES OR PERSONAL INJURY.

Warranty Conditions

All ceiling products must be installed and maintained in accordance with Armstrong written installation instructions for that product in effect at the time of installation and best industry practice. Prior to installation, the ceiling product must be kept clean and dry, in an environment that is between 32° F (0° C) and 120° F (49° C) and not subject to Abnormal Conditions.

For HumiGuard® Plus: Installation of the products shall be carried out where the temperature is between 32° F (0° C) and 120° F (49° C). It is not necessary for the area to be enclosed or for heating, ventilation and air conditioning (HVAC) systems to be functioning. All wet work (plastering, concrete, etc.) must be complete and dry.

For HumiGuard Max: HumiGuard Max's sag performance warranty extends to installations where the ceiling product is exposed to chemical fumes, extreme temperatures up to 120° F (49° C) (including steam up to 275° F (135° C)) and 100% RH, including standing water applications so long as the product is installed with either Stainless Steel Prelude® Plus, Aluminum Prelude® Plus or Prelude® Plus XL® Fireguard® suspension systems. For swimming pools, install only with Aluminum PRELUDE Plus Suspension system. For outdoor soffits, canopies, and parking garages install with Prelude® XL® for Exterior Applications (wind uplift should be considered).

HumiGuard Max and HumiGuard Plus: The ceilings must be maintained to avoid excessive dirt or dust buildup that would provide a medium for microbial growth on ceiling panels. Microbial protection does not extend beyond the treated surface as received from the factory, and does not protect other materials that contact the treated surface such as supported insulation materials.

How do you get service?

You must notify Armstrong World Industries of any product failure covered by this warranty within 30 days of first observation of failure by writing to the following address: Armstrong World Industries, Inc., P.O. Box 3001, Lancaster, PA 17604, or call us at 1 877 276-7876. Reference to Armstrong in this section shall mean, for the United States, Armstrong World Industries, Inc., P.O. Box 3001, Lancaster, PA 17604; and shall mean, for Canada: Armstrong World Industries, Canada, Ltd., 255 Montpellier blvd., Saint-Laurent, Montreal, Quebec, H4N 2G3.

How does state law apply?

This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. Some jurisdictions do not allow exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the limitation or exclusion herein may not apply to you.

All trademarks used herein are the property of AWI Licensing LLC and/or its affiliates
© 2026 AWI Licensing LLC

armstrong.com/commercial

Armstrong®
World Industries

BPCS-5342-1026